

Hoss™ 4X4 VXL (Model 90076-4) Parts List

Parts shown in bold are optional accessories. Part categories and individual part listings are arranged alphabetically.

	Bearings & Bushings	5136X	Differential oil kit (1 each: 10K, 30K, 50K weights)
4607	Ball bearings (5x11x4mm) (8)	6788	Differential, front (complete with pinion gear and differential
4612	Ball bearings (3X17X4mm) (0)		plastics) (fits 1/10-scale Rally & 4X4 VXL models: Slash,
2728	Ball bearings (5x8x2.5mm) (2)	6789	Stampede®, Rustler®) (13/37 ratio) Differential, rear (complete with pinion gear and differential
5119A	Ball bearings, black rubber sealed (10x15x4mm) (2)	0703	plastics) (fits 1/10-scale Rally & 4X4 VXL models: Slash,
5119	Ball bearings, blue rubber sealed (10x15x4mm) (2)		Stampede®, Rustler®) (13/37 ratio)
5120	Ball bearings, blue rubber sealed (12x18x4mm) (2)	6783	Gear set, center differential (output gears (2)/ spider gears (4)/ spider
5116	Ball bearings, blue rubber sealed (5x11x4mm) (2)	00001	gear shaft (2))
5114	Ball bearings, blue rubber sealed (5x8x2.5mm) (2)	6882X	Gear set, differential (output gears (2)/ spider gears (2)/ spider gear
5117 5118	Ball bearings, blue rubber sealed (6x12x4mm) (2) Ball bearings, blue rubber sealed (8x16x5mm) (2)	6781	shaft, carrier support) Housing, center differential (aluminum)/ x-ring gaskets (2)/ ring
1985	PTFE-coated washers, 5x8x0.5mm (20) (use with ball bearings)	0.0.	gear gasket/ bushings (2)/ 5x10x0.5mm PTFE-coated washers
1000	Body & Accessories		(2)/ 2.5x8 CCS (4)
1000		9081	Housing, center differential/x-ring gaskets (2)/ 5x10x0.5 PTFE-
1926 1726	Antenna caps, vinyl (2)/ antenna spool	0004	coated washer (1)/ 2.5x8 CCS (4)
9015	Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1) Body mounts, front & rear/ 3x12mm CS (4)/ 3x12mm shoulder screw	6881 6880	Housings, differential, front Housings, differential, rear
3010	(2)/ 3x10mm flat-head machine screw (6)/ 3x12mm BCS (1)	6782	Output gears, center differential, hardened steel (2)
9010	Body reinforcement set #9011	5379X	Ring gear, differential/ pinion gear, differential
9013	Body support/ 3x12mm CS (4) / (fits #9011 body)	5379R	Ring gear, differential/ pinion gear, differential (machined, spiral
9011	Body, Hoss™ 4X4 (clear, requires painting)/ window, grille, lights		cut) (front)
22112	decal sheet	6879R	Ring gear, differential/ pinion gear, differential (machined, spiral
9011G	Body, Hoss TM 4X4 VXL, green/ window, grille, lights decal sheet	0070	cut) (rear)
	(assembled with front & rear body mounts and rear body support for clipless mounting)	6879	Ring gear, differential/ pinion gear, differential (rear)
9011A	Body, Hoss™ 4X4 VXL, orange/ window, grille, lights decal sheet	3965 1647	Screws, 2.5x8mm cap-head machine (6) Silicone grease
	(assembled with front & rear body mounts and rear body support for	1047	
	clipless mounting)		Driveline Components
9011X	Body, Hoss™ 4X4, ProGraphix® (Graphics are printed, requires	5119A	Ball bearings, black rubber sealed (10x15x4mm) (2)
2514	paint & final color application)/ window, grille, lights decal sheet Decal sheet, racing sponsors	5119	Ball bearings, blue rubber sealed (10x15x4mm) (2)
9950	Official Team Traxxas® racing decal set (flag logo/ 6-color)	5116 9059X	Ball bearings, blue rubber sealed (5x11x4mm) (2) Cross pin (2)/ drive pin (2) (repairs 1 axle shaft)
9017	Skid plate, roof (body) (black) (left & right)/ 3x8mm CS (4)	6758	Differential output shaft (for steel constant-velocity driveshafts)
9012	Tailgate protector/ 3x10mm flat-head screw (3)	0.00	(2)
	Center Driveline	9057X	Differential output shafts, steel-splined constant-velocity (2)
5119A		6828A	Differential output yoke assembly, extreme heavy duty (2) (left or
5119A 5119	Ball bearings, black rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (10x15x4mm) (2)		right, front or rear) (assembled with external-splined half shaft)
5120	Ball bearings, blue rubber sealed (10x16x4mm) (2)	6851A	Driveshaft assembly, front, extreme heavy duty (1) (left or right) (fully
5116	Ball bearings, blue rubber sealed (5x11x4mm) (2)	6852A	assembled, ready to install)/ screw pin (1) Driveshaft assembly, rear, extreme heavy duty (1) (left or right) (fully
5117	Ball bearings, blue rubber sealed (6x12x4mm) (2)	000ZA	assembled, ready to install)/ screw pin (1)
9041	Cover, center driveshaft (clear)	6765	Driveshaft, center, 6061-T6 aluminum (blue-anodized) (189mm)
6877	Cover, gear/ motor wire hold-down clip	6765G	Driveshaft, center, 6061-T6 aluminum (green-anodized) (189mm)
7477	Cover, gear/ wire retainer	6765A	Driveshaft, center, 6061-T6 aluminum (orange-anodized)
6888	Drive hub, center, rear (1)/ 4x3 GS (1)	07050	(189mm)
6888X 9090	Drive hub, front, hardened steel (1)/ screw pin (1) Gear adapter, fixed	6765R 6767	Driveshaft, center, 6061-T6 aluminum (red-anodized) (189mm) Driveshaft, center, plastic, (black)/ screw pin
5148	Grease, white lithium	6851R	Driveshafts, front, steel-spline constant-velocity (complete
6890	Plate, motor	000111	assembly) (2)
6890X	Plate, motor, 6061-T6 aluminum (blue-anodized)	9051X	Driveshafts, front, steel-spline constant-velocity (complete
2575	Screws, 3x6mm button-head machine (hex drive) (6)		assembly) (2)
2554	Screws, 3x6mm cap-head machine (hex drive) (6)	6852R	Driveshafts, rear, steel-spline constant-velocity (complete
3932	Screws, 3x6mm flat-head machine (hex drive) (6)	00E2V	assembly) (2)
1647	Silicone grease	9052X	Driveshafts, rear, steel-spline constant-velocity (complete assembly) (2)
	Chassis & Attachments	9055X	Half shaft, external splined (steel-spline constant velocity) (1)
9026	Battery hold-down (2)/ battery clip/ hold-down post/ screw pin/ pivot	6750	Half shaft, external splined (steel-spline constant-velocity) (1)
	post screw	9056X	Half shaft, internal splined (steel-spline constant velocity) (1)
6724	Box, receiver (sealed)/ foam pad/ 2.5x8mm CS (4)/ 3x10mm CS (2)	6751	Half shaft, internal splined (steel-spline constant-velocity) (1)
9096	Bumper, front (with LED lights) (replacement for #9035 front	9058X	Rebuild kit, steel-splined constant-velocity driveshafts (includes
9035	bumper) Bumper, front/ bumper support	^===	pins and hardware for one axle shaft)
9097	Bumper, rear (with LED lights) (replacement for #9036 rear	6757	Rebuild kit, steel-splined constant-velocity driveshafts (includes pins, dustboots, lube, and hardware)
0001	bumper)	6854A	Stub axle assembly, front, outer, extreme heavy duty (1) (left or
9036	Bumper, rear/ bumper mount, rear/ bumper support, rear	000-171	right) (assembled with internal-splined half shaft)
9022	Chassis	6853A	Stub axle assembly, rear, outer, extreme heavy duty (1) (left or
9023	Nerf bars, chassis (2)		right) (assembled with internal-splined half shaft)
9078	Wheelie bar (assembled)	6754	Stub axle, front, 5mm (steel-splined constant-velocity
	Differential Components	00547	driveshaft) (1)
5119	Ball bearings, blue rubber sealed (10x15x4mm) (2)	9054X	Stub axle, front, steel-splined constant velocity (1)
5117	Ball bearings, blue rubber sealed (6x12x4mm) (2)	6753	Stub axle, rear, 5mm (steel-splined constant-velocity driveshaft) (1)
5118	Ball bearings, blue rubber sealed (8x16x5mm) (2)	9053X	Stub axle, rear, steel-splined constant velocity (1)
5381	Carrier, differential/ x-ring gaskets (2)/ ring gear gasket/ 6x10x0.5 TW	1654	Wheel hubs, hex (2)/ stub axle pins (2)
6780A	Center differential, complete (fits Hoss™ 4X4 VXL)	1654X	Wheel hubs, hex (blue-anodized, lightweight aluminum) (2)/ axle
6780	Differential kit, center (complete)		pins(4)

Page 2	Hoss™ 4X4 VXL	: TQi Traxxas Link	Enabled 2.4GHz	Radio & TSM (Model 90076-4) Parts List
--------	---------------	--------------------	----------------	---------------	---------------	--------------

	Front Suspension & Steering	1589	Double-sided adhesive tape (25mm x 25mm) (2)
2728	Ball bearings (5x8x2.5mm) (2)	2586	Screws, 3x15mm cap-head machine (hex drive) (6)
5114	Ball bearings, blue rubber sealed (5x8x2.5mm) (2)	2745	Nuts, 3mm nylon locking (12)
6823	Bulkhead tie bars, front & rear, aluminum (blue-anodized)	3647	Nuts, 4mm flanged nylon locking (steel, serrated) (8)
6823G	Bulkhead tie bars, front & rear, aluminum (green-anodized)	1747	Nuts, 4mm nylon locking (10)
6823R	Bulkhead tie bars, front & rear, aluminum (red-anodized)	1747A	Nuts, aluminum, flanged, serrated (4mm) (red-anodized) (4)
6830X	Bulkhead, front	1985 5525	PTFE-coated washers, 5x8x0.5mm (20) (use with ball bearings) Rod ends (12)/ hollow balls (12)
6735	Bumper, front/ skidplate, front (black)	2742X	Rod ends, short (6)/ hollow balls (6)
3643X	Camber links, front (TUBES blue-anodized, 7075-T6 aluminum,	3347	Screws, 2.5x5mm button-head machine (hex drive) (6)
	stronger than titanium) (83mm) (2)/ rod ends (4)/ aluminum	3215	Screws, 2.5x6mm cap-head machine (hex drive) (6)
	wrench (1) (#2579 3x15 BCS (4) required for installation)	3965	Screws, 2.5x8mm cap-head machine (6)
3643G	Camber links, front (TUBES green-anodized, 7075-T6 aluminum,	2577	Screws, 3x10mm button-head machine (hex drive) (6)
	stronger than titanium) (83mm) (2)/ rod ends (4)/ aluminum wrench (1) (#2579 3x15 BCS (4) required for installation)	2578	Screws, 3x12mm button-head machine (hex drive) (6)
3643R	Camber links, front (TUBES red-anodized, 7075-T6 aluminum,	2552	Screws, 3x12mm countersunk machine (6) (hex drive)
55.5.1	stronger than titanium) (83mm) (2)/ rod ends (4)/ aluminum	2579	Screws, 3x15mm button-head machine (hex drive) (6)
	wrench (1) (#2579 3x15 BCS (4) required for installation)	3646	Screws, 3x15mm flat-head machine (hex drive) (6)
6832X	Caster blocks (c-hubs), 6061-T6 aluminum (blue-anodized), left &	2583	Screws, 3x18mm button-head machine (hex drive) (6)
	right	2580	Screws, 3x20mm button-head machine (hex drive) (6)
6832G	Caster blocks (c-hubs), 6061-T6 aluminum (green-anodized), left	2591	Screws, 3x23mm button-head machine (hex drive) (6)
6832A	& right Caster blocks (c-hubs), 6061-T6 aluminum (orange-anodized),	2582	Screws, 3x30mm button-head machine (hex drive) (6)
0032A	left & right	2592 2575	Screws, 3x40mm button-head machine (hex drive) (6) Screws, 3x6mm button-head machine (hex drive) (6)
6832R	Caster blocks (c-hubs), 6061-T6 aluminum (red-anodized), left &	2534	Screws, 3x6mm countersunk machine (6) (hex drive)
	right	3932	Screws, 3x6mm flat-head machine (hex drive) (6)
6832	Caster blocks (c-hubs), left & right	2576	Screws, 3x8mm button-head machine (hex drive) (6)
6845A	Drag link, machined 6061-T6 aluminum (blue-anodized)	3931	Screws, 3x8mm flat-head machine (hex drive) (6)
6845G	Drag link, machined 6061-T6 aluminum (green-anodized)	3936	Screws, 4x10mm button-head machine (hex drive) (6)
6845T	Drag link, machined 6061-T6 aluminum (orange-anodized)	3937	Screws, 4x12mm button-head machine (hex drive) (6)
6845R	Drag link, machined 6061-T6 aluminum (red-anodized)	2542	Screws, 4x12mm countersunk machine (hex drive) (6)
6851A	Driveshaft assembly, front, extreme heavy duty (1) (left or right) (fully	3938	Screws, 4x14mm button-head machine (hex drive) (6)
6851R	assembled, ready to install)/ screw pin (1)	2546	Screws, 4x15mm countersunk machine (hex drive) (6)
003 IK	Driveshafts, front, steel-spline constant-velocity (complete assembly) (2)	2743	Set (grub) screws, 3mm hardened (12)
7438	Linkage, steering	3642X	Shoulder screws, Ultra Shocks (3x12 hex drive) (6)
6739	Shock tower, front	2754	Stub axle pins (4)
6739X	Shock tower, front, 7075-T6 aluminum (blue-anodized) (1)/ body	2748X	Tool set (includes 1.5mm & 2.5mm hex wrenches/ 4-way wrench/ 4mm and 8mm wrench/ U-joint wrench)
	mount bracket (1)	2746	Washers, 3x6mm metal (12)
6739G	Shock tower, front, 7075-T6 aluminum (green-anodized) (1)/ body	2140	LED Lights
	mount bracket (1)		
6739R	Shock tower, front, 7075-T6 aluminum (red-anodized) (1)/ body	9096	Bumper, front (with LED lights) (replacement for #9035 front
	mount bracket (1)		bumper)
68/5Y	Steering hellcranks/ serve saver/ serve saver spring/ serve spring	9097	Rumper rear (with LED lights) (replacement for #9036 rear
6845X	Steering bellcranks/ servo saver/ servo saver spring/ servo spring retainer/servo horn, steering	9097	Bumper, rear (with LED lights) (replacement for #9036 rear bumper)
6845X 6837X	retainer/servo horn, steering		bumper)
		9097 6541X	
6837X	retainer/servo horn, steering Steering blocks, 6061-T6 aluminum (blue-anodized), left & right		bumper) Connector, power tap (with cable)/ 2.6x8 BCS (2) (use #6549 power tap for telemetry voltage) LED light set, complete (includes front and rear bumpers with
6837X 6837G 6837A	retainer/servo horn, steering Steering blocks, 6061-T6 aluminum (blue-anodized), left & right Steering blocks, 6061-T6 aluminum (green-anodized), left & right Steering blocks, 6061-T6 aluminum (orange-anodized), left & right	6541X	bumper) Connector, power tap (with cable)/ 2.6x8 BCS (2) (use #6549 power tap for telemetry voltage) LED light set, complete (includes front and rear bumpers with LED lights, 3-volt accessory power supply, and power tap
6837X 6837G 6837A 6837R	retainer/servo horn, steering Steering blocks, 6061-T6 aluminum (blue-anodized), left & right Steering blocks, 6061-T6 aluminum (green-anodized), left & right Steering blocks, 6061-T6 aluminum (orange-anodized), left & right Steering blocks, 6061-T6 aluminum (red-anodized), left & right	6541X	bumper) Connector, power tap (with cable)/ 2.6x8 BCS (2) (use #6549 power tap for telemetry voltage) LED light set, complete (includes front and rear bumpers with LED lights, 3-volt accessory power supply, and power tap connector (with cable) (fits #9011 body)
6837X 6837G 6837A 6837R 6837	retainer/servo horn, steering Steering blocks, 6061-T6 aluminum (blue-anodized), left & right Steering blocks, 6061-T6 aluminum (green-anodized), left & right Steering blocks, 6061-T6 aluminum (orange-anodized), left & right Steering blocks, 6061-T6 aluminum (red-anodized), left & right Steering blocks, left & right	6541X	bumper) Connector, power tap (with cable)/ 2.6x8 BCS (2) (use #6549 power tap for telemetry voltage) LED light set, complete (includes front and rear bumpers with LED lights, 3-volt accessory power supply, and power tap
6837X 6837G 6837A 6837R	retainer/servo horn, steering Steering blocks, 6061-T6 aluminum (blue-anodized), left & right Steering blocks, 6061-T6 aluminum (green-anodized), left & right Steering blocks, 6061-T6 aluminum (orange-anodized), left & right Steering blocks, 6061-T6 aluminum (red-anodized), left & right Steering blocks, left & right Stub axle assembly, front, outer, extreme heavy duty (1) (left or	6541X	bumper) Connector, power tap (with cable)/ 2.6x8 BCS (2) (use #6549 power tap for telemetry voltage) LED light set, complete (includes front and rear bumpers with LED lights, 3-volt accessory power supply, and power tap connector (with cable) (fits #9011 body)
6837X 6837G 6837A 6837R 6837 6854A	retainer/servo horn, steering Steering blocks, 6061-T6 aluminum (blue-anodized), left & right Steering blocks, 6061-T6 aluminum (green-anodized), left & right Steering blocks, 6061-T6 aluminum (orange-anodized), left & right Steering blocks, 6061-T6 aluminum (red-anodized), left & right Steering blocks, left & right Stub axle assembly, front, outer, extreme heavy duty (1) (left or right) (assembled with internal-splined half shaft)	6541X 9095 1726 2260	bumper) Connector, power tap (with cable)/ 2.6x8 BCS (2) (use #6549 power tap for telemetry voltage) LED light set, complete (includes front and rear bumpers with LED lights, 3-volt accessory power supply, and power tap connector (with cable) (fits #9011 body) **Includes** Includes** Includ
6837X 6837G 6837A 6837R 6837	retainer/servo horn, steering Steering blocks, 6061-T6 aluminum (blue-anodized), left & right Steering blocks, 6061-T6 aluminum (green-anodized), left & right Steering blocks, 6061-T6 aluminum (orange-anodized), left & right Steering blocks, 6061-T6 aluminum (red-anodized), left & right Steering blocks, left & right Stub axle assembly, front, outer, extreme heavy duty (1) (left or	6541X 9095 1726	bumper) Connector, power tap (with cable)/ 2.6x8 BCS (2) (use #6549 power tap for telemetry voltage) LED light set, complete (includes front and rear bumpers with LED lights, 3-volt accessory power supply, and power tap connector (with cable) (fits #9011 body) MOTO'S & FIGGITONIGS Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1) BEC assembly (complete) Cooling fan kit (with shroud) (fits #3351R and #3461 motors)
6837X 6837G 6837A 6837R 6837 6854A	retainer/servo horn, steering Steering blocks, 6061-T6 aluminum (blue-anodized), left & right Steering blocks, 6061-T6 aluminum (green-anodized), left & right Steering blocks, 6061-T6 aluminum (orange-anodized), left & right Steering blocks, 6061-T6 aluminum (red-anodized), left & right Steering blocks, left & right Stub axle assembly, front, outer, extreme heavy duty (1) (left or right) (assembled with internal-splined half shaft) Stub axle, front, 5mm (steel-splined constant-velocity	9095 1726 2260 3456	bumper) Connector, power tap (with cable)/ 2.6x8 BCS (2) (use #6549 power tap for telemetry voltage) LED light set, complete (includes front and rear bumpers with LED lights, 3-volt accessory power supply, and power tap connector (with cable) (fits #9011 body) ***ICOTS & ICOTTOTION** Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1) BEC assembly (complete) Cooling fan kit (with shroud) (fits #3351R and #3461 motors) (requires #3458 heat sink to mount)
6837X 6837G 6837A 6837R 6837 6854A	retainer/servo horn, steering Steering blocks, 6061-T6 aluminum (blue-anodized), left & right Steering blocks, 6061-T6 aluminum (green-anodized), left & right Steering blocks, 6061-T6 aluminum (orange-anodized), left & right Steering blocks, 6061-T6 aluminum (red-anodized), left & right Steering blocks, left & right Stub axle assembly, front, outer, extreme heavy duty (1) (left or right) (assembled with internal-splined half shaft) Stub axle, front, 5mm (steel-splined constant-velocity driveshaft) (1)	6541X 9095 1726 2260 3456 3340	bumper) Connector, power tap (with cable)/ 2.6x8 BCS (2) (use #6549 power tap for telemetry voltage) LED light set, complete (includes front and rear bumpers with LED lights, 3-volt accessory power supply, and power tap connector (with cable) (fits #9011 body) ***IDIOTS & FERTONIES** Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1) BEC assembly (complete) Cooling fan kit (with shroud) (fits #3351R and #3461 motors) (requires #3458 heat sink to mount) Cooling fan, Velineon® VXL-3s ESC
6837X 6837G 6837A 6837R 6837 6854A 6754 3655P 3655R 3655G	retainer/servo horn, steering Steering blocks, 6061-T6 aluminum (blue-anodized), left & right Steering blocks, 6061-T6 aluminum (green-anodized), left & right Steering blocks, 6061-T6 aluminum (orange-anodized), left & right Steering blocks, 6061-T6 aluminum (red-anodized), left & right Steering blocks, left & right Stub axle assembly, front, outer, extreme heavy duty (1) (left or right) (assembled with internal-splined half shaft) Stub axle, front, 5mm (steel-splined constant-velocity driveshaft) (1) Suspension arms, blue, front/rear (left & right), heavy duty (2) Suspension arms, green, front/rear (left & right), heavy duty (2)	6541X 9095 1726 2260 3456 3340 9090	bumper) Connector, power tap (with cable)/ 2.6x8 BCS (2) (use #6549 power tap for telemetry voltage) LED light set, complete (includes front and rear bumpers with LED lights, 3-volt accessory power supply, and power tap connector (with cable) (fits #9011 body) ***Include Colors & Fetton CS** Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1) BEC assembly (complete) Cooling fan kit (with shroud) (fits #3351R and #3461 motors) (requires #3458 heat sink to mount) Cooling fan, Velineon® VXL-3s ESC Gear adapter, fixed
6837X 6837G 6837A 6837R 6837 6854A 6754 3655P 3655P 3655G 3655G	retainer/servo horn, steering Steering blocks, 6061-T6 aluminum (blue-anodized), left & right Steering blocks, 6061-T6 aluminum (green-anodized), left & right Steering blocks, 6061-T6 aluminum (orange-anodized), left & right Steering blocks, 6061-T6 aluminum (red-anodized), left & right Steering blocks, left & right Stub axle assembly, front, outer, extreme heavy duty (1) (left or right) (assembled with internal-splined half shaft) Stub axle, front, 5mm (steel-splined constant-velocity driveshaft) (1) Suspension arms, blue, front/rear (left & right), heavy duty (2) Suspension arms, green, front/rear (left & right), heavy duty (2) Suspension arms, orange, front/rear (left & right), heavy duty (2)	6541X 9095 1726 2260 3456 3340 9090 2072A	bumper) Connector, power tap (with cable)/ 2.6x8 BCS (2) (use #6549 power tap for telemetry voltage) LED light set, complete (includes front and rear bumpers with LED lights, 3-volt accessory power supply, and power tap connector (with cable) (fits #9011 body) ***ICLOS 8.** ICLIONICS** Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1) BEC assembly (complete) Cooling fan kit (with shroud) (fits #3351R and #3461 motors) (requires #3458 heat sink to mount) Cooling fan, Velineon® VXL-3s ESC Gear adapter, fixed Gear set (for 2070, 2075 servos)
6837X 6837G 6837A 6837R 6837 6854A 6754 3655P 3655R 3655G 3655T 3655L	retainer/servo horn, steering Steering blocks, 6061-T6 aluminum (blue-anodized), left & right Steering blocks, 6061-T6 aluminum (green-anodized), left & right Steering blocks, 6061-T6 aluminum (orange-anodized), left & right Steering blocks, 6061-T6 aluminum (red-anodized), left & right Steering blocks, left & right Stub axle assembly, front, outer, extreme heavy duty (1) (left or right) (assembled with internal-splined half shaft) Stub axle, front, 5mm (steel-splined constant-velocity driveshaft) (1) Suspension arms, blue, front/rear (left & right), heavy duty (2) Suspension arms, green, front/rear (left & right), heavy duty (2) Suspension arms, orange, front/rear (left & right), heavy duty (2) Suspension arms, red, front/rear (left & right), heavy duty (2)	6541X 9095 1726 2260 3456 3340 9090 2072A 2072X	bumper) Connector, power tap (with cable)/ 2.6x8 BCS (2) (use #6549 power tap for telemetry voltage) LED light set, complete (includes front and rear bumpers with LED lights, 3-volt accessory power supply, and power tap connector (with cable) (fits #9011 body) ***Includes** **Includes** **Inc
6837X 6837G 6837A 6837R 6837 6854A 6754 3655P 3655R 3655G 3655T 3655L 3655A	retainer/servo horn, steering Steering blocks, 6061-T6 aluminum (blue-anodized), left & right Steering blocks, 6061-T6 aluminum (green-anodized), left & right Steering blocks, 6061-T6 aluminum (orange-anodized), left & right Steering blocks, 6061-T6 aluminum (red-anodized), left & right Steering blocks, left & right Stub axle assembly, front, outer, extreme heavy duty (1) (left or right) (assembled with internal-splined half shaft) Stub axle, front, 5mm (steel-splined constant-velocity driveshaft) (1) Suspension arms, blue, front/rear (left & right), heavy duty (2) Suspension arms, green, front/rear (left & right), heavy duty (2) Suspension arms, orange, front/rear (left & right), heavy duty (2) Suspension arms, red, front/rear (left & right), heavy duty (2) Suspension arms, white, front/rear (left & right), heavy duty (2)	6541X 9095 1726 2260 3456 3340 9090 2072A 2072X 2252	bumper) Connector, power tap (with cable)/ 2.6x8 BCS (2) (use #6549 power tap for telemetry voltage) LED light set, complete (includes front and rear bumpers with LED lights, 3-volt accessory power supply, and power tap connector (with cable) (fits #9011 body) MOTOTS & FIGGITONICS Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1) BEC assembly (complete) Cooling fan kit (with shroud) (fits #3351R and #3461 motors) (requires #3458 heat sink to mount) Cooling fan, Velineon® VXL-3s ESC Gear adapter, fixed Gear set (for 2070, 2075 servos) Gear set, metal (for 2070, 2075 servos) Gear set, metal (for 2250, 2255 servos)
6837X 6837G 6837A 6837R 6837 6854A 6754 3655P 3655R 3655G 3655T 3655L 3655A 6834	retainer/servo horn, steering Steering blocks, 6061-T6 aluminum (blue-anodized), left & right Steering blocks, 6061-T6 aluminum (green-anodized), left & right Steering blocks, 6061-T6 aluminum (orange-anodized), left & right Steering blocks, 6061-T6 aluminum (red-anodized), left & right Steering blocks, left & right Steering blocks, left & right Stub axle assembly, front, outer, extreme heavy duty (1) (left or right) (assembled with internal-splined half shaft) Stub axle, front, 5mm (steel-splined constant-velocity driveshaft) (1) Suspension arms, blue, front/rear (left & right), heavy duty (2) Suspension arms, green, front/rear (left & right), heavy duty (2) Suspension arms, orange, front/rear (left & right), heavy duty (2) Suspension arms, red, front/rear (left & right), heavy duty (2) Suspension arms, white, front/rear (left & right), heavy duty (2) Suspension pin set, complete (front and rear)	6541X 9095 1726 2260 3456 3340 9090 2072A 2072X	bumper) Connector, power tap (with cable)/ 2.6x8 BCS (2) (use #6549 power tap for telemetry voltage) LED light set, complete (includes front and rear bumpers with LED lights, 3-volt accessory power supply, and power tap connector (with cable) (fits #9011 body) ***Includes** **Includes** **Inc
6837X 6837G 6837A 6837R 6837 6854A 6754 3655P 3655R 3655G 3655T 3655L 3655A	retainer/servo horn, steering Steering blocks, 6061-T6 aluminum (blue-anodized), left & right Steering blocks, 6061-T6 aluminum (green-anodized), left & right Steering blocks, 6061-T6 aluminum (orange-anodized), left & right Steering blocks, 6061-T6 aluminum (red-anodized), left & right Steering blocks, left & right Stub axle assembly, front, outer, extreme heavy duty (1) (left or right) (assembled with internal-splined half shaft) Stub axle, front, 5mm (steel-splined constant-velocity driveshaft) (1) Suspension arms, blue, front/rear (left & right), heavy duty (2) Suspension arms, green, front/rear (left & right), heavy duty (2) Suspension arms, orange, front/rear (left & right), heavy duty (2) Suspension arms, red, front/rear (left & right), heavy duty (2) Suspension arms, white, front/rear (left & right), heavy duty (2) Suspension pin set, complete (front and rear) Sway bar kit (front and rear) (includes front and rear sway bars	6541X 9095 1726 2260 3456 3340 9090 2072A 2072X 2252 2072R	bumper) Connector, power tap (with cable)/ 2.6x8 BCS (2) (use #6549 power tap for telemetry voltage) LED light set, complete (includes front and rear bumpers with LED lights, 3-volt accessory power supply, and power tap connector (with cable) (fits #9011 body) ***MOTOTS & FIGETONIES** Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1) BEC assembly (complete) Cooling fan kit (with shroud) (fits #3351R and #3461 motors) (requires #3458 heat sink to mount) Cooling fan, Velineon® VXL-3s ESC Gear adapter, fixed Gear set (for 2070, 2075 servos) Gear set, metal (for 2070, 2075 servos) Gear set, metal (for 2250, 2255 servos) Gear set, metal, high speed (for 2070, 2075 servos)
6837X 6837G 6837A 6837R 6837 6854A 6754 3655P 3655R 3655G 3655T 3655L 3655A 6834 6898	retainer/servo horn, steering Steering blocks, 6061-T6 aluminum (blue-anodized), left & right Steering blocks, 6061-T6 aluminum (green-anodized), left & right Steering blocks, 6061-T6 aluminum (orange-anodized), left & right Steering blocks, 6061-T6 aluminum (red-anodized), left & right Steering blocks, left & right Stub axle assembly, front, outer, extreme heavy duty (1) (left or right) (assembled with internal-splined half shaft) Stub axle, front, 5mm (steel-splined constant-velocity driveshaft) (1) Suspension arms, blue, front/rear (left & right), heavy duty (2) Suspension arms, green, front/rear (left & right), heavy duty (2) Suspension arms, orange, front/rear (left & right), heavy duty (2) Suspension arms, red, front/rear (left & right), heavy duty (2) Suspension pin set, complete (front and rear) Sway bar kit (front and rear) (includes front and rear sway bars and adjustable linkage)	9095 1726 2260 3456 3340 9090 2072A 2072X 2252 2072R 3458 6860A	bumper) Connector, power tap (with cable)/ 2.6x8 BCS (2) (use #6549 power tap for telemetry voltage) LED light set, complete (includes front and rear bumpers with LED lights, 3-volt accessory power supply, and power tap connector (with cable) (fits #9011 body) **Includes** Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1) BEC assembly (complete) Cooling fan kit (with shroud) (fits #3351R and #3461 motors) (requires #3458 heat sink to mount) Cooling fan, Velineon® VXL-3s ESC Gear adapter, fixed Gear set (for 2070, 2075 servos) Gear set, metal (for 2070, 2075 servos) Gear set, metal (for 2250, 2255 servos) Gear set, metal, high speed (for 2070, 2075 servos) Heat sink (fits #3351R and #3461 motors) Motor mount (assembled with 3x6 flat-head machine screw)/ 3.0mm NL (1)
6837X 6837G 6837A 6837R 6837 6854A 6754 3655P 3655R 3655G 3655T 3655L 3655A 6834	retainer/servo horn, steering Steering blocks, 6061-T6 aluminum (blue-anodized), left & right Steering blocks, 6061-T6 aluminum (green-anodized), left & right Steering blocks, 6061-T6 aluminum (orange-anodized), left & right Steering blocks, 6061-T6 aluminum (red-anodized), left & right Steering blocks, left & right Stub axle assembly, front, outer, extreme heavy duty (1) (left or right) (assembled with internal-splined half shaft) Stub axle, front, 5mm (steel-splined constant-velocity driveshaft) (1) Suspension arms, blue, front/rear (left & right), heavy duty (2) Suspension arms, front/rear (left & right), heavy duty (2) Suspension arms, orange, front/rear (left & right), heavy duty (2) Suspension arms, white, front/rear (left & right), heavy duty (2) Suspension pin set, complete (front and rear) Sway bar kit (front and rear) (includes front and rear sway bars and adjustable linkage) Toe links (TUBES blue-anodized, 7075-T6 aluminum, stronger	9095 1726 2260 3456 3340 9090 2072A 2072X 2252 2072R 3458 6860A	bumper) Connector, power tap (with cable)/ 2.6x8 BCS (2) (use #6549 power tap for telemetry voltage) LED light set, complete (includes front and rear bumpers with LED lights, 3-volt accessory power supply, and power tap connector (with cable) (fits #9011 body) ***Includes** Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1) BEC assembly (complete) Cooling fan kit (with shroud) (fits #3351R and #3461 motors) (requires #3458 heat sink to mount) Cooling fan, Velineon® VXL-3s ESC Gear adapter, fixed Gear set (for 2070, 2075 servos) Gear set, metal (for 2250, 2255 servos) Gear set, metal (for 2250, 2255 servos) Gear set, metal (for 2250, 2255 servos) Heat sink (fits #3351R and #3461 motors) Motor mount (assembled with 3x6 flat-head machine screw)/ 3.0mm NL (1) Motor mount, 6061-T6 aluminum (blue-anodized)
6837X 6837G 6837A 6837R 6837 6854A 6754 3655P 3655R 3655G 3655T 3655L 3655A 6834 6898	retainer/servo horn, steering Steering blocks, 6061-T6 aluminum (blue-anodized), left & right Steering blocks, 6061-T6 aluminum (green-anodized), left & right Steering blocks, 6061-T6 aluminum (orange-anodized), left & right Steering blocks, 6061-T6 aluminum (red-anodized), left & right Steering blocks, left & right Stub axle assembly, front, outer, extreme heavy duty (1) (left or right) (assembled with internal-splined half shaft) Stub axle, front, 5mm (steel-splined constant-velocity driveshaft) (1) Suspension arms, blue, front/rear (left & right), heavy duty (2) Suspension arms, green, front/rear (left & right), heavy duty (2) Suspension arms, orange, front/rear (left & right), heavy duty (2) Suspension arms, red, front/rear (left & right), heavy duty (2) Suspension pin set, complete (front and rear) Sway bar kit (front and rear) (includes front and rear sway bars and adjustable linkage)	9095 1726 2260 3456 3340 9090 2072A 2072X 2252 2072R 3458 6860A	bumper) Connector, power tap (with cable)/ 2.6x8 BCS (2) (use #6549 power tap for telemetry voltage) LED light set, complete (includes front and rear bumpers with LED lights, 3-volt accessory power supply, and power tap connector (with cable) (fits #9011 body) MOTOTS & FIGETONICS Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1) BEC assembly (complete) Cooling fan kit (with shroud) (fits #3351R and #3461 motors) (requires #3458 heat sink to mount) Cooling fan, Velineon® VXL-3s ESC Gear adapter, fixed Gear set (for 2070, 2075 servos) Gear set, metal (for 2070, 2075 servos) Gear set, metal (for 2250, 2255 servos) Gear set, metal (for 2250, 2255 servos) Heat sink (fits #3351R and #3461 motors) Motor mount (assembled with 3x6 flat-head machine screw)/ 3.0mm NL (1) Motor mount, 6061-T6 aluminum (blue-anodized) Motor, Velineon® 540XL, 2400Kv 70mm, brushless (assembled with
6837X 6837G 6837A 6837R 6837 6854A 6754 3655P 3655R 3655G 3655T 3655L 3655A 6834 6898	retainer/servo horn, steering Steering blocks, 6061-T6 aluminum (blue-anodized), left & right Steering blocks, 6061-T6 aluminum (green-anodized), left & right Steering blocks, 6061-T6 aluminum (orange-anodized), left & right Steering blocks, 6061-T6 aluminum (red-anodized), left & right Steering blocks, left & right Stub axle assembly, front, outer, extreme heavy duty (1) (left or right) (assembled with internal-splined half shaft) Stub axle, front, 5mm (steel-splined constant-velocity driveshaft) (1) Suspension arms, blue, front/rear (left & right), heavy duty (2) Suspension arms, front/rear (left & right), heavy duty (2) Suspension arms, orange, front/rear (left & right), heavy duty (2) Suspension arms, red, front/rear (left & right), heavy duty (2) Suspension arms, white, front/rear (left & right), heavy duty (2) Suspension pin set, complete (front and rear) Sway bar kit (front and rear) (includes front and rear sway bars and adjustable linkage) Toe links (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (87mm) (2)/ rod ends (4)/ aluminum wrench (1)	9095 1726 2260 3456 3340 9090 2072A 2072X 2252 2072R 3458 6860A	bumper) Connector, power tap (with cable)/ 2.6x8 BCS (2) (use #6549 power tap for telemetry voltage) LED light set, complete (includes front and rear bumpers with LED lights, 3-volt accessory power supply, and power tap connector (with cable) (fits #9011 body) MOTOTS & FIGETONIES Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1) BEC assembly (complete) Cooling fan kit (with shroud) (fits #3351R and #3461 motors) (requires #3458 heat sink to mount) Cooling fan, Velineon® VXL-3s ESC Gear adapter, fixed Gear set (for 2070, 2075 servos) Gear set, metal (for 2070, 2075 servos) Gear set, metal (for 2250, 2255 servos) Gear set, metal, high speed (for 2070, 2075 servos) Heat sink (fits #3351R and #3461 motors) Motor mount (assembled with 3x6 flat-head machine screw)/ 3.0mm NL (1) Motor mount, 6061-T6 aluminum (blue-anodized) Motor, Velineon® 540XL, 2400Kv 70mm, brushless (assembled with 6.5mm gold-plated bullet connectors) (for Maxx®/Hoss™) (not for use
6837X 6837G 6837A 6837R 6837 6854A 6754 3655P 3655R 3655G 3655T 3655L 3655A 6834 6898	retainer/servo horn, steering Steering blocks, 6061-T6 aluminum (blue-anodized), left & right Steering blocks, 6061-T6 aluminum (green-anodized), left & right Steering blocks, 6061-T6 aluminum (orange-anodized), left & right Steering blocks, 6061-T6 aluminum (red-anodized), left & right Steering blocks, left & right Steering blocks, left & right Stub axle assembly, front, outer, extreme heavy duty (1) (left or right) (assembled with internal-splined half shaft) Stub axle, front, 5mm (steel-splined constant-velocity driveshaft) (1) Suspension arms, blue, front/rear (left & right), heavy duty (2) Suspension arms, front/rear (left & right), heavy duty (2) Suspension arms, orange, front/rear (left & right), heavy duty (2) Suspension arms, red, front/rear (left & right), heavy duty (2) Suspension arms, white, front/rear (left & right), heavy duty (2) Suspension arms, white, front/rear (left & right), heavy duty (2) Suspension pin set, complete (front and rear) Sway bar kit (front and rear) (includes front and rear sway bars and adjustable linkage) Toe links (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (87mm) (2)/ rod ends (4)/ aluminum wrench (1) Toe links (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (87mm) (2)/ rod ends (4)/ aluminum wrench (1)	9095 1726 2260 3456 3340 9090 2072A 2072X 2252 2072R 3458 6860A 6860R 3461	bumper) Connector, power tap (with cable)/ 2.6x8 BCS (2) (use #6549 power tap for telemetry voltage) LED light set, complete (includes front and rear bumpers with LED lights, 3-volt accessory power supply, and power tap connector (with cable) (fits #9011 body) ***ICCITES** **ICCITOTICS** Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1) BEC assembly (complete) Cooling fan kit (with shroud) (fits #3351R and #3461 motors) (requires #3458 heat sink to mount) Cooling fan, Velineon® VXL-3s ESC Gear adapter, fixed Gear set (for 2070, 2075 servos) Gear set, metal (for 2070, 2075 servos) Gear set, metal (for 2250, 2255 servos) Gear set, metal, high speed (for 2070, 2075 servos) Heat sink (fits #3351R and #3461 motors) Motor mount (assembled with 3x6 flat-head machine screw)/ 3.0mm NL (1) Motor mount, 6061-T6 aluminum (blue-anodized) Motor, Velineon® 540XL, 2400Kv 70mm, brushless (assembled with 6.5mm gold-plated bullet connectors) (for Maxx®/Hoss™) (not for use in marine models)
6837X 6837G 6837A 6837R 6837 6854A 6754 3655P 3655R 3655G 3655T 3655L 3655A 6834 6898 6742X 6742G	retainer/servo horn, steering Steering blocks, 6061-T6 aluminum (blue-anodized), left & right Steering blocks, 6061-T6 aluminum (green-anodized), left & right Steering blocks, 6061-T6 aluminum (orange-anodized), left & right Steering blocks, 6061-T6 aluminum (red-anodized), left & right Steering blocks, left & right Steering blocks, left & right Stub axle assembly, front, outer, extreme heavy duty (1) (left or right) (assembled with internal-splined half shaft) Stub axle, front, 5mm (steel-splined constant-velocity driveshaft) (1) Suspension arms, blue, front/rear (left & right), heavy duty (2) Suspension arms, front/rear (left & right), heavy duty (2) Suspension arms, orange, front/rear (left & right), heavy duty (2) Suspension arms, orange, front/rear (left & right), heavy duty (2) Suspension arms, white, front/rear (left & right), heavy duty (2) Suspension pin set, complete (front and rear) Sway bar kit (front and rear) (includes front and rear sway bars and adjustable linkage) Toe links (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (87mm) (2)/ rod ends (4)/ aluminum wrench (1) Toe links (TUBES reed-anodized, 7075-T6 aluminum, stronger than titanium) (87mm) (2)/ rod ends (4)/ aluminum wrench (1) Toe links (TUBES reed-anodized, 7075-T6 aluminum, stronger than titanium) (87mm) (2)/ rod ends (4)/ aluminum wrench (1)	9095 1726 2260 3456 3340 9090 2072A 2072X 2252 2072R 3458 6860A 6860R 3461	bumper) Connector, power tap (with cable)/ 2.6x8 BCS (2) (use #6549 power tap for telemetry voltage) LED light set, complete (includes front and rear bumpers with LED lights, 3-volt accessory power supply, and power tap connector (with cable) (fits #9011 body) **Include The Telemetry of the T
6837X 6837G 6837A 6837R 6837 6854A 6754 3655P 3655R 3655G 3655T 3655L 3655A 6834 6898 6742X	retainer/servo horn, steering Steering blocks, 6061-T6 aluminum (blue-anodized), left & right Steering blocks, 6061-T6 aluminum (green-anodized), left & right Steering blocks, 6061-T6 aluminum (orange-anodized), left & right Steering blocks, 6061-T6 aluminum (red-anodized), left & right Steering blocks, left & right Stub axle assembly, front, outer, extreme heavy duty (1) (left or right) (assembled with internal-splined half shaft) Stub axle, front, 5mm (steel-splined constant-velocity driveshaft) (1) Suspension arms, blue, front/rear (left & right), heavy duty (2) Suspension arms, front/rear (left & right), heavy duty (2) Suspension arms, orange, front/rear (left & right), heavy duty (2) Suspension arms, orange, front/rear (left & right), heavy duty (2) Suspension arms, white, front/rear (left & right), heavy duty (2) Suspension pin set, complete (front and rear) Sway bar kit (front and rear) (includes front and rear sway bars and adjustable linkage) Toe links (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (87mm) (2)/ rod ends (4)/ aluminum wrench (1) Toe links (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (87mm) (2)/ rod ends (4)/ aluminum wrench (1) Toe links (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (87mm) (2)/ rod ends (4)/ aluminum wrench (1) Turnbuckles, camber link, 49mm (82mm center to center) (assembled	9095 1726 2260 3456 3340 9090 2072A 2072X 2252 2072R 3458 6860A 6860R 3461 6890 6890X	bumper) Connector, power tap (with cable)/ 2.6x8 BCS (2) (use #6549 power tap for telemetry voltage) LED light set, complete (includes front and rear bumpers with LED lights, 3-volt accessory power supply, and power tap connector (with cable) (fits #9011 body) ***Includes** **Includes** **In
6837X 6837G 6837A 6837R 6837 6854A 6754 3655P 3655R 3655G 3655T 3655L 3655A 6834 6898 6742X 6742G 6742R	retainer/servo horn, steering Steering blocks, 6061-T6 aluminum (blue-anodized), left & right Steering blocks, 6061-T6 aluminum (green-anodized), left & right Steering blocks, 6061-T6 aluminum (orange-anodized), left & right Steering blocks, 6061-T6 aluminum (red-anodized), left & right Steering blocks, left & right Steering blocks, left & right Stub axle assembly, front, outer, extreme heavy duty (1) (left or right) (assembled with internal-splined half shaft) Stub axle, front, 5mm (steel-splined constant-velocity driveshaft) (1) Suspension arms, blue, front/rear (left & right), heavy duty (2) Suspension arms, green, front/rear (left & right), heavy duty (2) Suspension arms, orange, front/rear (left & right), heavy duty (2) Suspension arms, red, front/rear (left & right), heavy duty (2) Suspension arms, white, front/rear (left & right), heavy duty (2) Suspension pin set, complete (front and rear) Sway bar kit (front and rear) (includes front and rear sway bars and adjustable linkage) Toe links (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (87mm) (2)/ rod ends (4)/ aluminum wrench (1) Toe links (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (87mm) (2)/ rod ends (4)/ aluminum wrench (1) Toe links (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (87mm) (2)/ rod ends (4)/ aluminum wrench (1) Toe links (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (87mm) (2)/ rod ends (4)/ aluminum wrench (1) Turnbuckles, camber link, 49mm (82mm center to center) (assembled with rod ends and hollow balls) (1 left, 1 right)	9095 1726 2260 3456 3340 9090 2072A 2072X 2252 2072R 3458 6860A 6860R 3461	bumper) Connector, power tap (with cable)/ 2.6x8 BCS (2) (use #6549 power tap for telemetry voltage) LED light set, complete (includes front and rear bumpers with LED lights, 3-volt accessory power supply, and power tap connector (with cable) (fits #9011 body) **Include The Telemetry of the T
6837X 6837G 6837A 6837R 6837 6854A 6754 3655P 3655R 3655G 3655T 3655L 3655A 6834 6898 6742X 6742G	retainer/servo horn, steering Steering blocks, 6061-T6 aluminum (blue-anodized), left & right Steering blocks, 6061-T6 aluminum (green-anodized), left & right Steering blocks, 6061-T6 aluminum (orange-anodized), left & right Steering blocks, 6061-T6 aluminum (red-anodized), left & right Steering blocks, left & right Steering blocks, left & right Stub axle assembly, front, outer, extreme heavy duty (1) (left or right) (assembled with internal-splined half shaft) Stub axle, front, 5mm (steel-splined constant-velocity driveshaft) (1) Suspension arms, blue, front/rear (left & right), heavy duty (2) Suspension arms, green, front/rear (left & right), heavy duty (2) Suspension arms, orange, front/rear (left & right), heavy duty (2) Suspension arms, red, front/rear (left & right), heavy duty (2) Suspension arms, white, front/rear (left & right), heavy duty (2) Suspension pin set, complete (front and rear) Sway bar kit (front and rear) (includes front and rear sway bars and adjustable linkage) Toe links (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (87mm) (2)/ rod ends (4)/ aluminum wrench (1) Toe links (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (87mm) (2)/ rod ends (4)/ aluminum wrench (1) Toe links (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (87mm) (2)/ rod ends (4)/ aluminum wrench (1) Toe links (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (87mm) (2)/ rod ends (4)/ aluminum wrench (1) Toe links (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (87mm) (2)/ rod ends (4)/ aluminum wrench (1) Toe links (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (87mm) (2)/ rod ends (4)/ aluminum wrench (1) Turnbuckles, camber link, 49mm (82mm center to center) (assembled with rod ends and hollow balls) (1 left, 1 right) Turnbuckles, camber links, 58mm (assembled with rod ends and	9095 1726 2260 3456 3340 9090 2072A 2072X 2252 2072R 3458 6860A 6860R 3461	bumper) Connector, power tap (with cable)/ 2.6x8 BCS (2) (use #6549 power tap for telemetry voltage) LED light set, complete (includes front and rear bumpers with LED lights, 3-volt accessory power supply, and power tap connector (with cable) (fits #9011 body) MOTOTS & FIGGITONICS Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1) BEC assembly (complete) Cooling fan kit (with shroud) (fits #3351R and #3461 motors) (requires #3458 heat sink to mount) Cooling fan, Velineon® VXL-3s ESC Gear adapter, fixed Gear set (for 2070, 2075 servos) Gear set, metal (for 2070, 2075 servos) Gear set, metal (for 2250, 2255 servos) Gear set, metal (for 2250, 2255 servos) Heat sink (fits #3351R and #3461 motors) Motor mount (assembled with 3x6 flat-head machine screw)/ 3.0mm NL (1) Motor mount, 6061-T6 aluminum (blue-anodized) Motor, Velineon® 540XL, 2400Kv 70mm, brushless (assembled with 6.5mm gold-plated bullet connectors) (for Maxx®/Hoss™) (not for use in marine models) Plate, motor Plate, motor, 6061-T6 aluminum (blue-anodized) Rebuild kit, Velineon® 3500 and 540XL (includes plastic endbell,
6837X 6837G 6837A 6837R 6837 6854A 6754 3655P 3655R 3655G 3655T 3655L 3655A 6834 6898 6742X 6742G 6742R	steering blocks, 6061-T6 aluminum (blue-anodized), left & right Steering blocks, 6061-T6 aluminum (green-anodized), left & right Steering blocks, 6061-T6 aluminum (orange-anodized), left & right Steering blocks, 6061-T6 aluminum (red-anodized), left & right Steering blocks, 6061-T6 aluminum (red-anodized), left & right Steering blocks, left & right Steering blocks, left & right Stub axle assembly, front, outer, extreme heavy duty (1) (left or right) (assembled with internal-splined half shaft) Stub axle, front, 5mm (steel-splined constant-velocity driveshaft) (1) Suspension arms, blue, front/rear (left & right), heavy duty (2) Suspension arms, front/rear (left & right), heavy duty (2) Suspension arms, orange, front/rear (left & right), heavy duty (2) Suspension arms, red, front/rear (left & right), heavy duty (2) Suspension arms, white, front/rear (left & right), heavy duty (2) Suspension pin set, complete (front and rear) Sway bar kit (front and rear) (includes front and rear sway bars and adjustable linkage) Toe links (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (87mm) (2)/ rod ends (4)/ aluminum wrench (1) Toe links (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (87mm) (2)/ rod ends (4)/ aluminum wrench (1) Turnbuckles, camber link, 49mm (82mm center to center) (assembled with rod ends and hollow balls) (1 left, 1 right) Turnbuckles, camber links, 58mm (assembled with rod ends and hollow balls) (2)	9095 1726 2260 3456 3340 9090 2072A 2072X 2252 2072R 3458 6860A 6860R 3461 6890 6890X 3352R	bumper) Connector, power tap (with cable)/ 2.6x8 BCS (2) (use #6549 power tap for telemetry voltage) LED light set, complete (includes front and rear bumpers with LED lights, 3-volt accessory power supply, and power tap connector (with cable) (fits #9011 body) ***ICCITES** **ECCITON** **ECCI
6837X 6837G 6837A 6837R 6837 6854A 6754 3655P 3655R 3655G 3655T 3655L 3655A 6834 6898 6742X 6742G 6742R 3643	Steering blocks, 6061-T6 aluminum (blue-anodized), left & right Steering blocks, 6061-T6 aluminum (green-anodized), left & right Steering blocks, 6061-T6 aluminum (orange-anodized), left & right Steering blocks, 6061-T6 aluminum (red-anodized), left & right Steering blocks, 6061-T6 aluminum (red-anodized), left & right Steering blocks, left & right Stub axle assembly, front, outer, extreme heavy duty (1) (left or right) (assembled with internal-splined half shaft) Stub axle, front, 5mm (steel-splined constant-velocity driveshaft) (1) Suspension arms, blue, front/rear (left & right), heavy duty (2) Suspension arms, green, front/rear (left & right), heavy duty (2) Suspension arms, orange, front/rear (left & right), heavy duty (2) Suspension arms, red, front/rear (left & right), heavy duty (2) Suspension arms, white, front/rear (left & right), heavy duty (2) Suspension pin set, complete (front and rear) Sway bar kit (front and rear) (includes front and rear sway bars and adjustable linkage) Toe links (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (87mm) (2)/ rod ends (4)/ aluminum wrench (1) Toe links (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (87mm) (2)/ rod ends (4)/ aluminum wrench (1) Toe links (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (87mm) (2)/ rod ends (4)/ aluminum wrench (1) Toe links (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (87mm) (2)/ rod ends (4)/ aluminum wrench (1) Toe links (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (87mm) (2)/ rod ends (4)/ aluminum wrench (1) Tor links (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (87mm) (2)/ rod ends (4)/ aluminum wrench (1) Tor links (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (87mm) (2)/ rod ends (4)/ aluminum wrench (1)	9095 1726 2260 3456 3340 9090 2072A 2072X 2252 2072R 3458 6860A 6860R 3461 6890 6890X 3352R 3347 3932	bumper) Connector, power tap (with cable)/ 2.6x8 BCS (2) (use #6549 power tap for telemetry voltage) LED light set, complete (includes front and rear bumpers with LED lights, 3-volt accessory power supply, and power tap connector (with cable) (fits #9011 body) ***Includes** **Includes** **Antenna**, tube (1)/ vinyl antenna cap (1)/ wire retainer (1) BEC assembly (complete) Cooling fan kit (with shroud) (fits #3351R and #3461 motors) (requires #3458 heat sink to mount) Cooling fan, Velineon® VXL-3s ESC Gear adapter, fixed Gear set (for 2070, 2075 servos) Gear set, metal (for 2070, 2075 servos) Gear set, metal (for 2250, 2255 servos) Gear set, metal (for 2250, 2255 servos) Heat sink (fits #3351R and #3461 motors) Motor mount (assembled with 3x6 flat-head machine screw)/ 3.0mm NL (1) **Motor mount**, 6061-T6 aluminum (blue-anodized) Motor, Velineon® 540XL, 2400Kv 70mm, brushless (assembled with 6.5mm gold-plated bullet connectors) (for Maxx®/Hoss™) (not for use in marine models) Plate, motor **Plate, motor, 6061-T6 aluminum (blue-anodized) Rebuild kit, Velineon® 3500 and 540XL (includes plastic endbell, 5x11x4mm ball bearings (2), 2.5x5mm BCS (with threadlock) (4), rear bushing) Screws, 2.5x5mm button-head machine (hex drive) (6) Screws, 3x6mm flat-head machine (hex drive) (6)
6837X 6837G 6837A 6837R 6837 6854A 6754 3655P 3655R 3655G 3655T 3655L 3655A 6834 6898 6742X 6742G 6742R 3643 5539	Steering blocks, 6061-T6 aluminum (blue-anodized), left & right Steering blocks, 6061-T6 aluminum (green-anodized), left & right Steering blocks, 6061-T6 aluminum (orange-anodized), left & right Steering blocks, 6061-T6 aluminum (red-anodized), left & right Steering blocks, 6061-T6 aluminum (red-anodized), left & right Steering blocks, left & right Stub axle assembly, front, outer, extreme heavy duty (1) (left or right) (assembled with internal-splined half shaft) Stub axle, front, 5mm (steel-splined constant-velocity driveshaft) (1) Suspension arms, blue, front/rear (left & right), heavy duty (2) Suspension arms, green, front/rear (left & right), heavy duty (2) Suspension arms, orange, front/rear (left & right), heavy duty (2) Suspension arms, red, front/rear (left & right), heavy duty (2) Suspension arms, white, front/rear (left & right), heavy duty (2) Suspension pin set, complete (front and rear) Sway bar kit (front and rear) (includes front and rear sway bars and adjustable linkage) Toe links (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (87mm) (2)/ rod ends (4)/ aluminum wrench (1) Toe links (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (87mm) (2)/ rod ends (4)/ aluminum wrench (1) Toe links (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (87mm) (2)/ rod ends (4)/ aluminum wrench (1) Turnbuckles, camber link, 49mm (82mm center to center) (assembled with rod ends and hollow balls) (1 left, 1 right) Turnbuckles, camber links, 58mm (assembled with rod ends and hollow balls) (2)	9095 1726 2260 3456 3340 9090 2072A 2072X 2252 2072R 3458 6860A 6860R 3461 6890 6890X 3352R 3347 3932 2254	bumper) Connector, power tap (with cable)/ 2.6x8 BCS (2) (use #6549 power tap for telemetry voltage) LED light set, complete (includes front and rear bumpers with LED lights, 3-volt accessory power supply, and power tap connector (with cable) (fits #9011 body) ***MOTOTS & FIGUTOTICS** Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1) BEC assembly (complete) Cooling fan kit (with shroud) (fits #3351R and #3461 motors) (requires #3458 heat sink to mount) Cooling fan, Velineon® VXL-3s ESC Gear adapter, fixed Gear set (for 2070, 2075 servos) Gear set, metal (for 2250, 2255 servos) Gear set, metal (for 2250, 2255 servos) Gear set, metal (for 2250, 2255 servos) Heat sink (fits #3351R and #3461 motors) Motor mount (assembled with 3x6 flat-head machine screw)/ 3.0mm NL (1) Motor mount, 6061-T6 aluminum (blue-anodized) Motor, Velineon® 540XL, 2400Kv 70mm, brushless (assembled with 6.5mm gold-plated bullet connectors) (for Maxx®/Hoss™) (not for use in marine models) Plate, motor Plate, motor, 6061-T6 aluminum (blue-anodized) Rebuild kit, Velineon® 3500 and 540XL (includes plastic endbell, 5x11x4mm ball bearings (2), 2.5x5mm BCS (with threadlock) (4), rear bushing) Screws, 2.5x5mm button-head machine (hex drive) (6) Screws, 3x6mm flat-head machine (hex drive) (6) Servo case, aluminum (blue-anodized) (middle) (for 2250 servo)
6837X 6837G 6837A 6837R 6837 6854A 6754 3655P 3655R 3655G 3655T 3655L 3655A 6834 6898 6742X 6742G 6742R 3643 5539	Steering blocks, 6061-T6 aluminum (blue-anodized), left & right Steering blocks, 6061-T6 aluminum (green-anodized), left & right Steering blocks, 6061-T6 aluminum (orange-anodized), left & right Steering blocks, 6061-T6 aluminum (red-anodized), left & right Steering blocks, 6061-T6 aluminum (red-anodized), left & right Steering blocks, left & right Stub axle assembly, front, outer, extreme heavy duty (1) (left or right) (assembled with internal-splined half shaft) Stub axle, front, 5mm (steel-splined constant-velocity driveshaft) (1) Suspension arms, blue, front/rear (left & right), heavy duty (2) Suspension arms, front/rear (left & right), heavy duty (2) Suspension arms, orange, front/rear (left & right), heavy duty (2) Suspension arms, red, front/rear (left & right), heavy duty (2) Suspension arms, white, front/rear (left & right), heavy duty (2) Suspension arms, white, front/rear (left & right), heavy duty (2) Suspension arms, white, front/rear (left & right), heavy duty (2) Suspension arms, white, front/rear (left & right), heavy duty (2) Suspension arms, white, front/rear (left & right), heavy duty (2) Suspension arms, white, front/rear (left & right), heavy duty (2) Suspension arms, orange, front/rear (left & right), heavy duty (2) Suspension arms, orange, front/rear (left & right), heavy duty (2) Suspension arms, orange, front/rear (left & right), heavy duty (2) Suspension arms, orange, front/rear (left & right), heavy duty (2) Suspension arms, orange, front/rear (left & right), heavy duty (2) Suspension arms, orange, front/rear (left & right), heavy duty (2) Suspension arms, orange, front/rear (left & right), heavy duty (2) Suspension arms, orange, front/rear (left & right), heavy duty (2) Suspension arms, orange, front/rear (left & right), heavy duty (2) Suspension arms, orange, front/rear (left & right), heavy duty (2) Suspension arms, orange, front/rear (left & right), heavy duty (2) Suspension arms, orange, front/rear (left & right), heavy duty (2) Suspension arms, orange, fr	6541X 9095 1726 2260 3456 3340 9090 2072A 2072X 2252 2072R 3458 6860A 6860R 3461 6890 6890X 3352R 3347 3932 2254 2253	bumper) Connector, power tap (with cable)/ 2.6x8 BCS (2) (use #6549 power tap for telemetry voltage) LED light set, complete (includes front and rear bumpers with LED lights, 3-volt accessory power supply, and power tap connector (with cable) (fits #9011 body) MOTOTS & FIGGITONICS Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1) BEC assembly (complete) Cooling fan kit (with shroud) (fits #3351R and #3461 motors) (requires #3458 heat sink to mount) Cooling fan, Velineon® VXL-3s ESC Gear adapter, fixed Gear set (for 2070, 2075 servos) Gear set, metal (for 2070, 2075 servos) Gear set, metal (for 2250, 2255 servos) Gear set, metal (for 2250, 2255 servos) Gear set, metal, high speed (for 2070, 2075 servos) Heat sink (fits #3351R and #3461 motors) Motor mount (assembled with 3x6 flat-head machine screw)/ 3.0mm NL (1) Motor mount, 6061-T6 aluminum (blue-anodized) Motor, Velineon® 540XL, 2400Kv 70mm, brushless (assembled with 6.5mm gold-plated bullet connectors) (for Maxx®/Hoss™) (not for use in marine models) Plate, motor Plate, motor Plate, motor, 6061-T6 aluminum (blue-anodized) Rebuild kit, Velineon® 3500 and 540XL (includes plastic endbell, 5x11x4mm ball bearings (2), 2.5x5mm BCS (with threadlock) (4), rear bushing) Screws, 2.5x5mm button-head machine (hex drive) (6) Screws, 3x6mm flat-head machine (hex drive) (6) Servo case, aluminum (blue-anodized) (middle) (for 2250 servo) Servo case, aluminum (red-anodized) (middle) (for 2255 servo)
6837X 6837G 6837A 6837R 6837 6854A 6754 3655P 3655R 3655G 3655T 3655L 3655A 6834 6898 6742X 6742G 6742R 3643 5539	Steering blocks, 6061-T6 aluminum (blue-anodized), left & right Steering blocks, 6061-T6 aluminum (green-anodized), left & right Steering blocks, 6061-T6 aluminum (orange-anodized), left & right Steering blocks, 6061-T6 aluminum (red-anodized), left & right Steering blocks, 6061-T6 aluminum (red-anodized), left & right Steering blocks, left & right Steering blocks, left & right Stub axle assembly, front, outer, extreme heavy duty (1) (left or right) (assembled with internal-splined half shaft) Stub axle, front, 5mm (steel-splined constant-velocity driveshaft) (1) Suspension arms, blue, front/rear (left & right), heavy duty (2) Suspension arms, front/rear (left & right), heavy duty (2) Suspension arms, green, front/rear (left & right), heavy duty (2) Suspension arms, red, front/rear (left & right), heavy duty (2) Suspension arms, white, front/rear (left & right), heavy duty (2) Suspension arms, white, front/rear (left & right), heavy duty (2) Suspension pin set, complete (front and rear) Sway bar kit (front and rear) (includes front and rear sway bars and adjustable linkage) Toe links (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (87mm) (2)/ rod ends (4)/ aluminum wrench (1) Toe links (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (87mm) (2)/ rod ends (4)/ aluminum wrench (1) Turnbuckles, camber link, 49mm (82mm center to center) (assembled with rod ends and hollow balls) (1 left, 1 right) Turnbuckles, camber links, 58mm (assembled with rod ends and hollow balls) (2)	9095 1726 2260 3456 3340 9090 2072A 2072X 2252 2072R 3458 6860A 6860R 3461 6890 6890X 3352R 3347 3932 2254	bumper) Connector, power tap (with cable)/ 2.6x8 BCS (2) (use #6549 power tap for telemetry voltage) LED light set, complete (includes front and rear bumpers with LED lights, 3-volt accessory power supply, and power tap connector (with cable) (fits #9011 body) MOTOTS & FIGCITONICS Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1) BEC assembly (complete) Cooling fan kit (with shroud) (fits #3351R and #3461 motors) (requires #3458 heat sink to mount) Cooling fan, Velineon® VXL-3s ESC Gear adapter, fixed Gear set (for 2070, 2075 servos) Gear set, metal (for 2070, 2075 servos) Gear set, metal (for 2250, 2255 servos) Gear set, metal, high speed (for 2070, 2075 servos) Heat sink (fits #3351R and #3461 motors) Motor mount (assembled with 3x6 flat-head machine screw)/ 3.0mm NL (1) Motor mount, 6061-T6 aluminum (blue-anodized) Motor, Velineon® 540XL, 2400Kv 70mm, brushless (assembled with 6.5mm gold-plated bullet connectors) (for Maxx®/Hoss™) (not for use in marine models) Plate, motor Plate, motor, 6061-T6 aluminum (blue-anodized) Rebuild kit, Velineon® 3500 and 540XL (includes plastic endbell, 5x11x4mm ball bearings (2), 2.5x5mm BCS (with threadlock) (4), rear bushing) Screws, 2.5x5mm button-head machine (hex drive) (6) Screws, 3x6mm flat-head machine (hex drive) (6) Screvs, 3x6mm flat-head machine (hex drive) (6) Servo case, aluminum (blue-anodized) (middle) (for 2250 servo) Servo case, plastic (top, middle, bottom)/ gaskets/ hardware (for
6837X 6837G 6837A 6837R 6837 6854A 6754 3655P 3655R 3655G 3655T 3655L 3655A 6834 6898 6742X 6742G 6742R 3643 5539	Steering blocks, 6061-T6 aluminum (blue-anodized), left & right Steering blocks, 6061-T6 aluminum (green-anodized), left & right Steering blocks, 6061-T6 aluminum (orange-anodized), left & right Steering blocks, 6061-T6 aluminum (red-anodized), left & right Steering blocks, left & right Stub axle assembly, front, outer, extreme heavy duty (1) (left or right) (assembled with internal-splined half shaft) Stub axle, front, 5mm (steel-splined constant-velocity driveshaft) (1) Suspension arms, blue, front/rear (left & right), heavy duty (2) Suspension arms, front/rear (left & right), heavy duty (2) Suspension arms, orange, front/rear (left & right), heavy duty (2) Suspension arms, red, front/rear (left & right), heavy duty (2) Suspension arms, white, front/rear (left & right), heavy duty (2) Suspension pin set, complete (front and rear) Sway bar kit (front and rear) (includes front and rear sway bars and adjustable linkage) Toe links (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (87mm) (2)/ rod ends (4)/ aluminum wrench (1) Toe links (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (87mm) (2)/ rod ends (4)/ aluminum wrench (1) Toe links (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (87mm) (2)/ rod ends (4)/ aluminum wrench (1) Turnbuckles, camber link, 49mm (82mm center to center) (assembled with rod ends and hollow balls) (1 left, 1 right) Turnbuckles, camber links, 58mm (assembled with rod ends and hollow balls) (2) Antenna caps, vinyl (2)/ antenna spool Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1) Screws, 3x8mm cap-head machine (hex drive) (6)/washers (6)/ wrench	6541X 9095 1726 2260 3456 3340 9090 2072A 2072X 2252 2072R 3458 6860A 6860R 3461 6890 6890X 3352R 3347 3932 2254 2253 2251	bumper) Connector, power tap (with cable)/ 2.6x8 BCS (2) (use #6549 power tap for telemetry voltage) LED light set, complete (includes front and rear bumpers with LED lights, 3-volt accessory power supply, and power tap connector (with cable) (fits #9011 body) **MOTOT'S & FIGETONICS** Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1) BEC assembly (complete) Cooling fan kit (with shroud) (fits #3351R and #3461 motors) (requires #3458 heat sink to mount) Cooling fan, Velineon® VXL-3s ESC Gear adapter, fixed Gear set (for 2070, 2075 servos) Gear set, metal (for 2070, 2075 servos) Gear set, metal (for 2250, 2255 servos) Gear set, metal, high speed (for 2070, 2075 servos) Heat sink (fits #3351R and #3461 motors) Motor mount (assembled with 3x6 flat-head machine screw)/ 3.0mm NL (1) Motor mount, 6061-T6 aluminum (blue-anodized) Motor, Velineon® 540XL, 2400Kv 70mm, brushless (assembled with 6.5mm gold-plated bullet connectors) (for Maxx®/Hoss™) (not for use in marine models) Plate, motor, 6061-T6 aluminum (blue-anodized) Rebuild kit, Velineon® 3500 and 540XL (includes plastic endbell, 5x11x4mm ball bearings (2), 2.5x5mm BCS (with threadlock) (4), rear bushing) Screws, 2.5x5mm button-head machine (hex drive) (6) Screvo, 3x6mm flat-head machine (hex drive) (6) Screvo case, aluminum (blue-anodized) (middle) (for 2255 servo) Servo case, plastic (top, middle, bottom)/ gaskets/ hardware (for 2250, 2255 servos)
6837X 6837G 6837A 6837R 6837 6854A 6754 3655P 3655R 3655G 3655L 3655A 6834 6898 6742X 6742G 6742R 3643 5539	Steering blocks, 6061-T6 aluminum (blue-anodized), left & right Steering blocks, 6061-T6 aluminum (green-anodized), left & right Steering blocks, 6061-T6 aluminum (orange-anodized), left & right Steering blocks, 6061-T6 aluminum (red-anodized), left & right Steering blocks, 6061-T6 aluminum (red-anodized), left & right Steering blocks, left & right Steering blocks, left & right Steering blocks, left & right Stub axle assembly, front, outer, extreme heavy duty (1) (left or right) (assembled with internal-splined half shaft) Stub axle, front, 5mm (steel-splined constant-velocity driveshaft) (1) Suspension arms, blue, front/rear (left & right), heavy duty (2) Suspension arms, front/rear (left & right), heavy duty (2) Suspension arms, orange, front/rear (left & right), heavy duty (2) Suspension arms, red, front/rear (left & right), heavy duty (2) Suspension arms, white, front/rear (left & right), heavy duty (2) Suspension pin set, complete (front and rear) Sway bar kit (front and rear) (includes front and rear sway bars and adjustable linkage) Toe links (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (87mm) (2)/ rod ends (4)/ aluminum wrench (1) Toe links (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (87mm) (2)/ rod ends (4)/ aluminum wrench (1) Toe links (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (87mm) (2)/ rod ends (4)/ aluminum wrench (1) Toe links (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (87mm) (2)/ rod ends (4)/ aluminum wrench (1) Toe links (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (87mm) (2)/ rod ends (4)/ aluminum wrench (1) Toe links (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (87mm) (2)/ rod ends (4)/ aluminum wrench (1) Toe links (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (87mm) (2)/ rod ends (4)/ aluminum wrench (1) Toe links (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (87mm) (2)/ rod ends (4)/ aluminum wrench (1) Toe links (TUBES the first	6541X 9095 1726 2260 3456 3340 9090 2072A 2072X 2252 2072R 3458 6860A 6860R 3461 6890 6890X 3352R 3347 3932 2254 2253 2251	bumper) Connector, power tap (with cable)/ 2.6x8 BCS (2) (use #6549 power tap for telemetry voltage) LED light set, complete (includes front and rear bumpers with LED lights, 3-volt accessory power supply, and power tap connector (with cable) (fits #9011 body) **MOTOT'S & FORTONICS** Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1) BEC assembly (complete) Cooling fan kit (with shroud) (fits #3351R and #3461 motors) (requires #3458 heat sink to mount) Cooling fan, Velineon® VXL-3s ESC Gear adapter, fixed Gear set (for 2070, 2075 servos) Gear set, metal (for 2070, 2075 servos) Gear set, metal (for 2250, 2255 servos) Gear set, metal, high speed (for 2070, 2075 servos) Heat sink (fits #3351R and #3461 motors) Motor mount (assembled with 3x6 flat-head machine screw)/ 3.0mm NL (1) Motor mount, 6061-T6 aluminum (blue-anodized) Motor, Velineon® 540XL, 2400Kv 70mm, brushless (assembled with 6.5mm gold-plated bullet connectors) (for Maxx®/Hoss™) (not for use in marine models) Plate, motor Plate, motor Plate, motor, 6061-T6 aluminum (blue-anodized) Rebuild kit, Velineon® 3500 and 540XL (includes plastic endbell, 5x11x4mm ball bearings (2), 2.5x5mm BCS (with threadlock) (4), rear bushing) Screws, 2.5x5mm button-head machine (hex drive) (6) Screws, 3x6mm flat-head machine (hex drive) (6) Screvo case, aluminum (blue-anodized) (middle) (for 2255 servo) Servo case, aluminum (red-anodized) (middle) (for 2255 servo) Servo case, plastic (top, middle, bottom)/ gaskets/ hardware (for 2250, 2255 servos) Servo case/gaskets (for 2056 and 2075 waterproof servos)
6837X 6837G 6837A 6837R 6837 6854A 6754 3655P 3655R 3655G 3655T 3655L 3655A 6834 6898 6742X 6742G 6742R 3643 5539	Steering blocks, 6061-T6 aluminum (blue-anodized), left & right Steering blocks, 6061-T6 aluminum (green-anodized), left & right Steering blocks, 6061-T6 aluminum (orange-anodized), left & right Steering blocks, 6061-T6 aluminum (red-anodized), left & right Steering blocks, left & right Stub axle assembly, front, outer, extreme heavy duty (1) (left or right) (assembled with internal-splined half shaft) Stub axle, front, 5mm (steel-splined constant-velocity driveshaft) (1) Suspension arms, blue, front/rear (left & right), heavy duty (2) Suspension arms, front/rear (left & right), heavy duty (2) Suspension arms, orange, front/rear (left & right), heavy duty (2) Suspension arms, red, front/rear (left & right), heavy duty (2) Suspension arms, white, front/rear (left & right), heavy duty (2) Suspension pin set, complete (front and rear) Sway bar kit (front and rear) (includes front and rear sway bars and adjustable linkage) Toe links (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (87mm) (2)/ rod ends (4)/ aluminum wrench (1) Toe links (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (87mm) (2)/ rod ends (4)/ aluminum wrench (1) Toe links (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (87mm) (2)/ rod ends (4)/ aluminum wrench (1) Turnbuckles, camber link, 49mm (82mm center to center) (assembled with rod ends and hollow balls) (1 left, 1 right) Turnbuckles, camber links, 58mm (assembled with rod ends and hollow balls) (2) Antenna caps, vinyl (2)/ antenna spool Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1) Screws, 3x8mm cap-head machine (hex drive) (6)/washers (6)/ wrench	6541X 9095 1726 2260 3456 3340 9090 2072A 2072X 2252 2072R 3458 6860A 6860R 3461 6890 6890X 3352R 3347 3932 2254 2253 2251	bumper) Connector, power tap (with cable)/ 2.6x8 BCS (2) (use #6549 power tap for telemetry voltage) LED light set, complete (includes front and rear bumpers with LED lights, 3-volt accessory power supply, and power tap connector (with cable) (fits #9011 body) **MOTOT'S & FORTONICS** Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1) BEC assembly (complete) Cooling fan kit (with shroud) (fits #3351R and #3461 motors) (requires #3458 heat sink to mount) Cooling fan, Velineon® VXL-3s ESC Gear adapter, fixed Gear set (for 2070, 2075 servos) Gear set, metal (for 2070, 2075 servos) Gear set, metal (for 2250, 2255 servos) Gear set, metal, high speed (for 2070, 2075 servos) Heat sink (fits #3351R and #3461 motors) Motor mount (assembled with 3x6 flat-head machine screw)/ 3.0mm NL (1) Motor mount, 6061-T6 aluminum (blue-anodized) Motor, Velineon® 540XL, 2400Kv 70mm, brushless (assembled with 6.5mm gold-plated bullet connectors) (for Maxx®/Hoss™) (not for use in marine models) Plate, motor Plate, motor, 6061-T6 aluminum (blue-anodized) Rebuild kit, Velineon® 3500 and 540XL (includes plastic endbell, 5x11x4mm ball bearings (2), 2.5x5mm BCS (with threadlock) (4), rear bushing) Screws, 2.5x5mm button-head machine (hex drive) (6) Screvo, 23x6mm flat-head machine (hex drive) (6) Servo case, aluminum (red-anodized) (middle) (for 2255 servo) Servo case, plastic (top, middle, bottom)/ gaskets/ hardware (for 2250, 2255 servos)

2252	Come digital high targets 000 seculars as (Classes (C. 11))	6500	Transmitter TO: Transce Limbth analysis 1.0.4001 bish as a fine
2250 2255	Servo, digital high-torque 330 coreless, metal gear (ball bearing), waterproof	6529 6530	Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 3- channel (transmitter only)
	Servo, digital high-torque 400 brushless, metal gear (ball bearing), waterproof		Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 4- channel (transmitter only)
2075X	Servo, digital high-torque, metal gear (ball bearing), waterproof	6511	Traxxas Link™ Wireless Module
2849X	Radio System, Batteries & Chargers 4000mAh 11.1v 3-Cell 25C LiPo Battery	90076-4	Ready-To-Race Model Hoss™ 4X4 VXL: 1/10 Scale Monster Truck with TQi Traxxas Link™
2872X	5000mAh 11.1v 3-Cell 25C LiPo Battery	90070-4	Enabled 2.4GHz Radio System & Traxxas Stability Management
2843X	5800mAh 7.4v 2-Cell 25C LiPo Battery		(TSM)®
2869X 2976	7600mAh 7.4v 2-Cell 25C LiPo Battery AC to DC converter, 40W		Rear Suspension
2938X	Adapter, Traxxas® iD® LiPo battery (adapts Traxxas iD batteries	6823 6823G	Bulkhead tie bars, front & rear, aluminum (blue-anodized)
00.40	to separate balance ports)	6823G 6823R	Bulkhead tie bars, front & rear, aluminum (green-anodized) Bulkhead tie bars, front & rear, aluminum (red-anodized)
2943 6548	Battery charge indicators (green (4), blue (4), gray (4)) Battery door, transmitter (replacement for #6516, 6517, 6528, 6529,	6829	Bulkhead, rear
	6530 transmitters)	3644X	Camber links, rear (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (73mm) (2)/ rod ends (4)/ aluminum
2914	Battery, Power Cell AA Alkaline (4)		wrench (1) (#2579 3x15 BCS (4) required for installation)
2923X 2940X	Battery, Power Cell, 3000mAh (NiMH, 7-C flat, 8.4V) Battery, Series 3 Power Cell, 3300mAh (NiMH, 7-C flat, 8.4V)	3644G	Camber links, rear (TUBES green-anodized 7075-T6 aluminum,
2950X	Battery, Series 4 Power Cell, 4200mAh (NiMH, 7-C flat, 8.4V)		stronger than titanium) (73mm) (2)/ rod ends (4)/ aluminum wrench (1) (#2579 3x15 BCS (4) required for installation)
2960X	Battery, Series 5 Power Cell, 5000mAh (NiMH, 7-C flat, 8.4V)	3644R	Camber links, rear (TUBES red-anodized, 7075-T6 aluminum,
2983	Battery/charger completer pack (includes #2969 2-amp NiMH peak detecting AC charger (1), #2923X 3000mAh 8.4V 7-cell NiMH		stronger than titanium) (73mm) (2)/ rod ends (4)/ aluminum wrench (1) (#2579 3x15 BCS (4) required for installation)
2992	battery (1)) Battery/charger completer pack (includes #2970 iD® charger (1),	1952X 1952G	Carriers, stub axle (blue-anodized 6061-T6 aluminum) (rear) (2) Carriers, stub axle (green-anodized 6061-T6 aluminum) (rear) (2)
2994	#2843X 5800mAh 7.4V 2-cell 25C LiPo battery (1)) Battery/charger completer pack (includes #2970 iD® charger (1),	1952G 1952T	Carriers, stub axle (orange-anodized 6061-T6 aluminum) (rear)
2004	#2849X 4000mAh 11.1v 3-Cell 25C LiPo Battery (1))	1952	(2) Carriers, stub axle (rear) (2)
2260	BEC assembly (complete)	1952A	Carriers, stub axle (red-anodized 6061-T6 aluminum) (rear) (2)
2975 2972	Charger, DC, 4 amp (6 - 7 cell, 7.2 - 8.4 volt, NiMH) Charger, EZ-Peak® Dual, 100W, NiMH/LiPo with iD® Auto Battery	6852A	Driveshaft assembly, rear, extreme heavy duty (1) (left or right) (fully
2973	Identification Charger, EZ-Peak® Live Dual, 200W, NiMH/LiPo with iD® Auto	6852R	assembled, ready to install)/ screw pin (1) Driveshafts, rear, steel-spline constant-velocity (complete assembly) (2)
	Battery Identification	6738	Shock tower, rear
2971	Charger, EZ-Peak® Live, 100W, NiMH/LiPo with iD® Auto Battery Identification	6738X	Shock tower, rear, 7075-T6 aluminum (blue-anodized) (1)/ body mount bracket (1)
2970	Charger, EZ-Peak® Plus, 4 amp, NiMH/LiPo with iD® Auto Battery Identification	6738G	Shock tower, rear, 7075-T6 aluminum (green-anodized) (1)/ body mount bracket (1)
6525 2978	Communication link, telemetry expander Fuse, charger, 5A (2) (for #2974, 2975, 2977)	6738R	Shock tower, rear, 7075-T6 aluminum (red-anodized) (1)/ body
2072A	Gear set (for 2070, 2075 servos)	6853A	mount bracket (1) Stub axle assembly, rear, outer, extreme heavy duty (1) (left or
2072X	Gear set, metal (for 2070, 2075 servos)		right) (assembled with internal-splined half shaft)
2252 2072R	Gear set, metal (for 2250, 2255 servos) Gear set, metal, high speed (for 2070, 2075 servos)	3655P 3655R	Suspension arms, blue, front/rear (left & right), heavy duty (2) Suspension arms, front/rear (left & right), heavy duty (2)
2968X	LiPo cell voltage checker/balancer (includes #2938X adapter for	3655G	Suspension arms, green, front/rear (left & right), heavy duty (2)
2968	Traxxas® iD® batteries) LiPo cell voltage checker/balancer (requires #2938X adapter for	3655T	Suspension arms, orange, front/rear (left & right), heavy duty (2)
2900	Traxxas® iD® batteries)	3655L 3655A	Suspension arms, red, front/rear (left & right), heavy duty (2) Suspension arms, white, front/rear (left & right), heavy duty (2)
6535	Mount, temperature sensor (electric motors)/ wire tie/ thermal	6834	Suspension pin set, complete (front and rear)
6533	pad Receiver, micro, TQi 2.4GHz with telemetry & TSM (5-channel)	6898	Sway bar kit (front and rear) (includes front and rear sway bars
3932	Screws, 3x6mm flat-head machine (hex drive) (6)	3644	and adjustable linkage) Turnbuckles, camber link, 39mm (69mm center to center) (assemble
6552	Seal kit, expander box (includes o-ring, seals, and silicone grease)	3044	with rod ends and hollow balls) (1 left, 1 right) (fits front & rear on Slash, rear on Slash 4X4)
6526	Sensor, auto-detectable, temperature		Shock Oil
6527 6521	Sensor, auto-detectable, voltage Sensor, temperature and voltage (long)	5031	Oil, shock (20 wt, 200 cSt, 60cc) (silicone)
2254	Servo case, aluminum (blue-anodized) (middle) (for 2250 servo)	5032	Oil, shock (30 wt, 350 cSt, 60cc) (silicone)
2253	Servo case, aluminum (red-anodized) (middle) (for 2255 servo)	5033	Oil, shock (40 wt, 500 cSt, 60cc) (silicone)
2251	Servo case, plastic (top, middle, bottom)/ gaskets/ hardware (for 2250, 2255 servos)	5034 5035	Oil, shock (50 wt, 600 cSt, 60cc) (silicone) Oil, shock (60 wt, 700 cSt, 60cc) (silicone)
2074	Servo case/gaskets (for 2056 and 2075 waterproof servos)	5036	Oil, shock (70 wt, 900 cSt, 60cc) (silicone)
2075R	Servo, digital high-speed, metal gear (ball bearing), waterproof	5037	Oil, shock (80 wt, 1,000 cSt, 60cc) (silicone)
2075 2250	Servo, digital high-torque (ball bearing), waterproof Servo, digital high-torque 330 coreless, metal gear (ball bearing), waterproof	5029 5038X	Shock oil bottle (60cc) (for mixing shock oil) Shock oil set (includes 20 wt, 30 wt, 40 wt, 50 wt, 60 wt, 70 wt, & 80 wt premium shock oils with spinning carousel rack)
2255	Servo, digital high-torque 400 brushless, metal gear (ball bearing), waterproof	1667 5038	Silicone shock oil (30 wt), 60cc Spinning carousel rack
2075X	Servo, digital high-torque, metal gear (ball bearing), waterproof		Shocks (GTR)
6553X	Telemetry expander 2.0 and GPS module 2.0, TQi radio system	7466X	Body, GTR long (hard-anodized, PTFE-coated aluminum) (1)
6550X 6551X	Telemetry expander 2.0, TQi radio system (for use only with #6551X GPS module) Telemetry GPS module 2.0, TQi radio system (for use only with	7466	Body, GTR long shock, aluminum (blue-anodized) (PTFE-coated bodies) (1)
6509R	#6550X telemetry expander) TQi 2.4 GHz High Output radio system, 2-channel, Traxxas Link™	7466G	Body, GTR long shock, aluminum (green-anodized) (PTFE-coated bodies) (1)
6507R	rigit 2.4 GHz High Output radio system, 2-channel, Iraxxas Link : enabled, TSM (2-ch transmitter, 5-ch micro receiver) TQi 2.4 GHz High Output radio system, 4-channel with Traxxas	7466A	Body, GTR long shock, aluminum (orange-anodized) (PTFE-coated bodies) (1)
0001K	Link™ Wireless Module, TSM (4-ch transmitter, 5-ch micro receiver)	7467X 7467	Body, GTR xx-long (hard-anodized, PTFE-coated aluminum) (1) Body, GTR xx-long shock, aluminum (blue-anodized) (PTFE-
6528	Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 2-	74670	coated bodies) (1)
	channel (transmitter only)	7467G	Body, GTR xx-long shock, aluminum (green-anodized) (PTFE-coated bodies) (1)

Page 4	Hoss™ 4X4 VXL: TQi Traxxas Link Enabled 2.4GHz	Radio 8	& TSM (Model 90076-4) Parts List
7467A	Body, GTR xx-long shock, aluminum (orange-anodized) (PTFE-coated bodies) (1)	3767P 3767X	Shock caps, aluminum (pink-anodized) (4) (fits all Ultra Shocks) Shock caps, aluminum (red-anodized) (4) (fits all Ultra Shocks)
7468	Caps and spring retainers, GTR long/xx-long shock (upper cap (2)/ hollow balls (4)/ bottom cap (2)/ upper retainer (2)/ lower	1664T 2656T	Shock shafts, hardened steel, titanium nitride coated (long) (2) Shock shafts, hardened steel, titanium nitride coated (xx-long)
7463	retainer (2)) Rebuild kit, GTR long/xx-long shocks (x-rings, bladders, pistons,	1664	(2) Shock shafts, steel, chrome finish (long) (2)
	piston nuts, shock rod ends, hollow balls) (renews 2 shocks)	2656	Shock shafts, steel, chrome finish (xx-long) (2)
5469 7464T	Rod ends (GTR shocks) (6) Shaft, GTR long, TiN-coated (2)	1765	Silicone diaphragms (4)
74641 7465T	Shaft, GTR xx-long, TiN-coated (2)	3769 3768	Spring pre-load spacers: 1mm (4)/ 2mm (2)/ 4mm (2)/ 8mm (2) Spring retainers, upper & lower (2)/ piston head set (2-hole (2)/ 3-hole
7461	Shocks, GTR long blue-anodized, PTFE-coated bodies with TiN shafts (fully assembled, without springs) (2)		(2))
7461G	Shocks, GTR long green-anodized, PTFE-coated bodies with TiN	3758 3758T	Springs, front (black) (2) Springs, front (blue) (2)
	shafts (fully assembled, without springs) (2)	3758A	Springs, front (green) (2)
7461X	Shocks, GTR long hard-anodized, PTFE-coated bodies with TiN shafts (assembled) (2) (without springs)	3758P	Springs, front (pink) (2)
7462	Shocks, GTR xx-long blue-anodized, PTFE-coated bodies with	6863 6864	Springs, front (progressive, +10% rate, pink) (2)
	TiN shafts (fully assembled, without springs) (2)	6862	Springs, front (progressive, +20% rate, blue) (2) Springs, front (progressive, -10% rate, green) (2)
7462G	Shocks, GTR xx-long green-anodized, PTFE-coated bodies with TiN shafts (fully assembled, without springs) (2)	6861	Springs, front (progressive, -20% rate, orange) (2)
7462X	Shocks, GTR xx-long hard-anodized, PTFE-coated bodies with	3758X	Springs, front (white) (2)
	TiN shafts (assembled) (2) (without springs)	6857 3757	Springs, front (white) (progressive rate) (2)
7440	Spring, shock, white (GTR long) (0.623 rate orange) (1 pair)	3757 3757T	Springs, rear (black) (2) Springs, rear (blue) (2)
7441 7444	Spring, shock, white (GTR long) (0.653 rate green) (1 pair) Spring, shock, white (GTR long) (0.767 rate black) (1 pair)	3757A	Springs, rear (green) (2)
7445	Spring, shock, white (GTR long) (0.810 rate pink) (1 pair)	3757P	Springs, rear (pink) (2)
7448	Spring, shock, white (GTR long) (0.892 rate blue) (1 pair)	6867	Springs, rear (progressive, +10% rate, pink) (2)
7442	Spring, shock, white (GTR xx-long) (0.711 rate orange) (1 pair)	6868 6866	Springs, rear (progressive, +20% rate, blue) (2) Springs, rear (progressive, -10% rate, green) (2)
7443 7446	Spring, shock, white (GTR xx-long) (0.762 rate green) (1 pair) Spring, shock, white (GTR xx-long) (0.874 rate black) (1 pair)	6865	Springs, rear (progressive, -20% rate, orange) (2)
7447	Spring, shock, white (GTR xx-long) (0.884 rate pink) (1 pair)	3757X	Springs, rear (white) (2)
7449	Spring, shock, white (GTR xx-long) (1.004 rate blue) (1 pair)	6858	Springs, rear (white) (progressive rate) (2)
	Shocks (Pro-level Aluminum)	3760	Ultra Shocks (black) (long) (complete w/ spring pre-load spacers & springs) (front) (2)
2664	Big Bore shock cylinder (long) (1)	3762	Ultra Shocks (black) (xx-long) (complete w/ spring pre-load
2666	Big Bore shock cylinder (XX-long) (1)	27604	spacers & springs) (rear) (2)
5862	Big Bore shocks (hard-anodized & PTFE-coated T6 aluminum) (assembled with TiN shafts and springs) (front & rear) (4)	3760A	Ultra Shocks (gray) (long) (complete w/ spring pre-load spacers & springs) (2)
2660	Big Bore shocks (long) (hard-anodized & PTFE-coated T6 aluminum) (assembled with TiN shafts) w/o springs (front) (2)	3762A	Ultra Shocks (gray) (xx-long) (complete w/ spring pre-load spacers & springs) (rear) (2)
2662	Big Bore shocks (XX-long) (hard-anodized & PTFE-coated T6 aluminum) (assembled with TiN shafts) w/o springs (rear) (2)		Spur Gears & Pinion Gears
2669	Piston head set (2-hole (2)/ 3-hole (2))/ shock mounting bushings	6877	Cover, gear/ motor wire hold-down clip
	& washers (2) (Big Bore Shocks)	9090 5641	Gear adapter, fixed Gear, 11-T pinion (0.8 metric pitch, compatible with 32-pitch) (fits
2362 1942	Rebuild kit, Ultra shocks (for 2 shocks) Rod ends (16 long & 4 short)/ hollow ball connectors (18)/ ball screws		5mm shaft)/ set screw Gear, 13-T pinion (0.8 metric pitch, compatible with 32-pitch) (fits
2742X	(2) Rod ends, short (6)/ hollow balls (6)	5642	5mm shaft)/ set screw
2667	Rod ends, short (6)/ hollow balls (6) Shock caps, aluminum (Big Bore Shocks) (2)	5640	5mm shaft)/ set screw Gear, 14-T pinion (0.8 metric pitch, compatible with 32-pitch) (fits
	Rod ends, short (6)/ hollow balls (6) Shock caps, aluminum (Big Bore Shocks) (2) Shock shafts, hardened steel, titanium nitride coated (long) (2) Shock shafts, hardened steel, titanium nitride coated (xx-long)		5mm shaft)/ set screw Gear, 14-T pinion (0.8 metric pitch, compatible with 32-pitch) (fits 5mm shaft)/ set screw Gear, 17-T pinion (0.8 metric pitch, compatible with 32-pitch) (fits
2667 1664T 2656T	Rod ends, short (6)/ hollow balls (6) Shock caps, aluminum (Big Bore Shocks) (2) Shock shafts, hardened steel, titanium nitride coated (long) (2) Shock shafts, hardened steel, titanium nitride coated (xx-long) (2)	5640	5mm shaft)/ set screw Gear, 14-T pinion (0.8 metric pitch, compatible with 32-pitch) (fits 5mm shaft)/ set screw Gear, 17-T pinion (0.8 metric pitch, compatible with 32-pitch) (fits 5mm shaft)/ set screw Gear, 18-T pinion (0.8 metric pitch, compatible with 32-pitch)
2667 1664T 2656T	Rod ends, short (6)/ hollow balls (6) Shock caps, aluminum (Big Bore Shocks) (2) Shock shafts, hardened steel, titanium nitride coated (long) (2) Shock shafts, hardened steel, titanium nitride coated (xx-long) (2) Shock shafts, steel, chrome finish (long) (2)	5640 5643 5644	5mm shaft)/ set screw Gear, 14-T pinion (0.8 metric pitch, compatible with 32-pitch) (fits 5mm shaft)/ set screw Gear, 17-T pinion (0.8 metric pitch, compatible with 32-pitch) (fits 5mm shaft)/ set screw Gear, 18-T pinion (0.8 metric pitch, compatible with 32-pitch) (hardened steel) (fits 5mm shaft)/ set screw
2667 1664T 2656T 1664 2656 1765	Rod ends, short (6)/ hollow balls (6) Shock caps, aluminum (Big Bore Shocks) (2) Shock shafts, hardened steel, titanium nitride coated (long) (2) Shock shafts, hardened steel, titanium nitride coated (xx-long) (2) Shock shafts, steel, chrome finish (long) (2) Shock shafts, steel, chrome finish (xx-long) (2) Silicone diaphragms (4)	5640 5643	5mm shaft)/ set screw Gear, 14-T pinion (0.8 metric pitch, compatible with 32-pitch) (fits 5mm shaft)/ set screw Gear, 17-T pinion (0.8 metric pitch, compatible with 32-pitch) (fits 5mm shaft)/ set screw Gear, 18-T pinion (0.8 metric pitch, compatible with 32-pitch)
2667 1664T 2656T 1664 2656	Rod ends, short (6)/ hollow balls (6) Shock caps, aluminum (Big Bore Shocks) (2) Shock shafts, hardened steel, titanium nitride coated (long) (2) Shock shafts, hardened steel, titanium nitride coated (xx-long) (2) Shock shafts, steel, chrome finish (long) (2) Shock shafts, steel, chrome finish (xx-long) (2) Silicone diaphragms (4) Spring retainers, upper & lower (2)/ spring pre-load spacers: 1mm (4)/ 1.5mm (2)/ 2mm (2)/ 4mm (2)/ 8mm (2) (Big Bore	5640 5643 5644	5mm shaft)/ set screw Gear, 14-T pinion (0.8 metric pitch, compatible with 32-pitch) (fits 5mm shaft)/ set screw Gear, 17-T pinion (0.8 metric pitch, compatible with 32-pitch) (fits 5mm shaft)/ set screw Gear, 18-T pinion (0.8 metric pitch, compatible with 32-pitch) (hardened steel) (fits 5mm shaft)/ set screw Gear, 20-T pinion (0.8 metric pitch, compatible with 32-pitch) (fits 5mm shaft)/ set screw Spur gear, steel, 50-tooth (0.8 metric pitch, compatible with 32-
2667 1664T 2656T 1664 2656 1765	Rod ends, short (6)/ hollow balls (6) Shock caps, aluminum (Big Bore Shocks) (2) Shock shafts, hardened steel, titanium nitride coated (long) (2) Shock shafts, hardened steel, titanium nitride coated (xx-long) (2) Shock shafts, steel, chrome finish (long) (2) Shock shafts, steel, chrome finish (xx-long) (2) Silicone diaphragms (4) Spring retainers, upper & lower (2)/ spring pre-load spacers:	5640 5643 5644 5646	5mm shaft)/ set screw Gear, 14-T pinion (0.8 metric pitch, compatible with 32-pitch) (fits 5mm shaft)/ set screw Gear, 17-T pinion (0.8 metric pitch, compatible with 32-pitch) (fits 5mm shaft)/ set screw Gear, 18-T pinion (0.8 metric pitch, compatible with 32-pitch) (hardened steel) (fits 5mm shaft)/ set screw Gear, 20-T pinion (0.8 metric pitch, compatible with 32-pitch) (fits 5mm shaft)/ set screw Spur gear, steel, 50-tooth (0.8 metric pitch, compatible with 32-pitch) (for center differential) Spur gear, steel, 54-tooth (0.8 metric pitch, compatible with 32-pitch)
2667 1664T 2656T 1664 2656 1765 2668	Rod ends, short (6)/ hollow balls (6) Shock caps, aluminum (Big Bore Shocks) (2) Shock shafts, hardened steel, titanium nitride coated (long) (2) Shock shafts, hardened steel, titanium nitride coated (xx-long) (2) Shock shafts, steel, chrome finish (long) (2) Shock shafts, steel, chrome finish (xx-long) (2) Silicone diaphragms (4) Spring retainers, upper & lower (2)/ spring pre-load spacers: 1mm (4)/ 1.5mm (2)/ 2mm (2)/ 4mm (2)/ 8mm (2) (Big Bore Shocks) Springs, front (progressive, +10% rate, pink) (2) Springs, front (progressive, +20% rate, blue) (2)	5640 5643 5644 5646 6842X	5mm shaft)/ set screw Gear, 14-T pinion (0.8 metric pitch, compatible with 32-pitch) (fits 5mm shaft)/ set screw Gear, 17-T pinion (0.8 metric pitch, compatible with 32-pitch) (fits 5mm shaft)/ set screw Gear, 18-T pinion (0.8 metric pitch, compatible with 32-pitch) (hardened steel) (fits 5mm shaft)/ set screw Gear, 20-T pinion (0.8 metric pitch, compatible with 32-pitch) (fits 5mm shaft)/ set screw Spur gear, steel, 50-tooth (0.8 metric pitch, compatible with 32-pitch) (for center differential) Spur gear, steel, 54-tooth (0.8 metric pitch, compatible with 32-pitch) (requires #6780 center differential)
2667 1664T 2656T 1664 2656 1765 2668 6863 6864 6862	Rod ends, short (6)/ hollow balls (6) Shock caps, aluminum (Big Bore Shocks) (2) Shock shafts, hardened steel, titanium nitride coated (long) (2) Shock shafts, hardened steel, titanium nitride coated (xx-long) (2) Shock shafts, steel, chrome finish (long) (2) Shock shafts, steel, chrome finish (xx-long) (2) Silicone diaphragms (4) Spring retainers, upper & lower (2)/ spring pre-load spacers: 1mm (4)/ 1.5mm (2)/ 2mm (2)/ 4mm (2)/ 8mm (2) (Big Bore Shocks) Springs, front (progressive, +10% rate, pink) (2) Springs, front (progressive, +20% rate, blue) (2) Springs, front (progressive, -10% rate, green) (2)	5640 5643 5644 5646 6842X 3956X	5mm shaft)/ set screw Gear, 14-T pinion (0.8 metric pitch, compatible with 32-pitch) (fits 5mm shaft)/ set screw Gear, 17-T pinion (0.8 metric pitch, compatible with 32-pitch) (fits 5mm shaft)/ set screw Gear, 18-T pinion (0.8 metric pitch, compatible with 32-pitch) (hardened steel) (fits 5mm shaft)/ set screw Gear, 20-T pinion (0.8 metric pitch, compatible with 32-pitch) (fits 5mm shaft)/ set screw Spur gear, steel, 50-tooth (0.8 metric pitch, compatible with 32-pitch) (for center differential) Spur gear, steel, 54-tooth (0.8 metric pitch, compatible with 32-pitch) (requires #6780 center differential)
2667 1664T 2656T 1664 2656 1765 2668 6863 6864 6862 6861	Rod ends, short (6)/ hollow balls (6) Shock caps, aluminum (Big Bore Shocks) (2) Shock shafts, hardened steel, titanium nitride coated (long) (2) Shock shafts, hardened steel, titanium nitride coated (xx-long) (2) Shock shafts, steel, chrome finish (long) (2) Shock shafts, steel, chrome finish (xx-long) (2) Silicone diaphragms (4) Spring retainers, upper & lower (2)/ spring pre-load spacers: 1mm (4)/ 1.5mm (2)/ 2mm (2)/ 4mm (2)/ 8mm (2) (Big Bore Shocks) Springs, front (progressive, +10% rate, pink) (2) Springs, front (progressive, +20% rate, blue) (2) Springs, front (progressive, -20% rate, orange) (2)	5640 5643 5644 5646 6842X	5mm shaft)/ set screw Gear, 14-T pinion (0.8 metric pitch, compatible with 32-pitch) (fits 5mm shaft)/ set screw Gear, 17-T pinion (0.8 metric pitch, compatible with 32-pitch) (fits 5mm shaft)/ set screw Gear, 18-T pinion (0.8 metric pitch, compatible with 32-pitch) (hardened steel) (fits 5mm shaft)/ set screw Gear, 20-T pinion (0.8 metric pitch, compatible with 32-pitch) (fits 5mm shaft)/ set screw Spur gear, steel, 50-tooth (0.8 metric pitch, compatible with 32-pitch) (for center differential) Spur gear, steel, 54-tooth (0.8 metric pitch, compatible with 32-pitch) (requires #6780 center differential)
2667 1664T 2656T 1664 2656 1765 2668 6863 6864 6862	Rod ends, short (6)/ hollow balls (6) Shock caps, aluminum (Big Bore Shocks) (2) Shock shafts, hardened steel, titanium nitride coated (long) (2) Shock shafts, hardened steel, titanium nitride coated (xx-long) (2) Shock shafts, steel, chrome finish (long) (2) Shock shafts, steel, chrome finish (xx-long) (2) Silicone diaphragms (4) Spring retainers, upper & lower (2)/ spring pre-load spacers: 1mm (4)/ 1.5mm (2)/ 2mm (2)/ 4mm (2)/ 8mm (2) (Big Bore Shocks) Springs, front (progressive, +10% rate, pink) (2) Springs, front (progressive, +20% rate, blue) (2) Springs, front (progressive, -10% rate, green) (2)	5640 5643 5644 5646 6842X 3956X	Gear, 14-T pinion (0.8 metric pitch, compatible with 32-pitch) (fits 5mm shaft)/ set screw Gear, 17-T pinion (0.8 metric pitch, compatible with 32-pitch) (fits 5mm shaft)/ set screw Gear, 18-T pinion (0.8 metric pitch, compatible with 32-pitch) (hardened steel) (fits 5mm shaft)/ set screw Gear, 20-T pinion (0.8 metric pitch, compatible with 32-pitch) (fits 5mm shaft)/ set screw Gear, 20-T pinion (0.8 metric pitch, compatible with 32-pitch) (for center differential) Spur gear, steel, 50-tooth (0.8 metric pitch, compatible with 32-pitch) (for center differential) Spur gear, steel, 54-tooth (0.8 metric pitch, compatible with 32-pitch) (requires #6780 center differential) Signification (0.8 metric pitch) (0.8 metric pitch) (1.8
2667 1664T 2656T 1664 2656 1765 2668 6863 6864 6862 6861 6857 6867 6868	Rod ends, short (6)/ hollow balls (6) Shock caps, aluminum (Big Bore Shocks) (2) Shock shafts, hardened steel, titanium nitride coated (long) (2) Shock shafts, hardened steel, titanium nitride coated (xx-long) (2) Shock shafts, steel, chrome finish (long) (2) Shock shafts, steel, chrome finish (xx-long) (2) Silicone diaphragms (4) Spring retainers, upper & lower (2)/ spring pre-load spacers: 1mm (4)/ 1.5mm (2)/ 2mm (2)/ 4mm (2)/ 8mm (2) (Big Bore Shocks) Springs, front (progressive, +10% rate, pink) (2) Springs, front (progressive, -10% rate, green) (2) Springs, front (progressive, -20% rate, orange) (2) Springs, front (white) (progressive rate) (2) Springs, rear (progressive, +10% rate, pink) (2) Springs, rear (progressive, +20% rate, blue) (2)	5640 5643 5644 5646 6842X 3956X 1552 2728 5114	5mm shaft)/ set screw Gear, 14-T pinion (0.8 metric pitch, compatible with 32-pitch) (fits 5mm shaft)/ set screw Gear, 17-T pinion (0.8 metric pitch, compatible with 32-pitch) (fits 5mm shaft)/ set screw Gear, 18-T pinion (0.8 metric pitch, compatible with 32-pitch) (hardened steel) (fits 5mm shaft)/ set screw Gear, 20-T pinion (0.8 metric pitch, compatible with 32-pitch) (fits 5mm shaft)/ set screw Spur gear, steel, 50-tooth (0.8 metric pitch, compatible with 32-pitch) (for center differential) Spur gear, steel, 54-tooth (0.8 metric pitch, compatible with 32-pitch) (requires #6780 center differential) Screws, 3x8mm cap-head machine (hex drive) (6)/washers (6)/wrench Ball bearings (5x8x2.5mm) (2) Ball bearings, blue rubber sealed (5x8x2.5mm) (2)
2667 1664T 2656T 1664 2656 1765 2668 6863 6864 6862 6861 6857 6867 6868 6866	Rod ends, short (6)/ hollow balls (6) Shock caps, aluminum (Big Bore Shocks) (2) Shock shafts, hardened steel, titanium nitride coated (long) (2) Shock shafts, hardened steel, titanium nitride coated (xx-long) (2) Shock shafts, steel, chrome finish (long) (2) Shock shafts, steel, chrome finish (xx-long) (2) Silicone diaphragms (4) Spring retainers, upper & lower (2)/ spring pre-load spacers: 1mm (4)/ 1.5mm (2)/ 2mm (2)/ 4mm (2)/ 8mm (2) (Big Bore Shocks) Springs, front (progressive, +10% rate, pink) (2) Springs, front (progressive, -10% rate, green) (2) Springs, front (white) (progressive rate) (2) Springs, rear (progressive, +10% rate, pink) (2) Springs, rear (progressive, +20% rate, blue) (2) Springs, rear (progressive, +20% rate, blue) (2) Springs, rear (progressive, -10% rate, pink) (2) Springs, rear (progressive, -10% rate, pine) (2)	5640 5643 5644 5646 6842X 3956X 1552 2728 5114 6845A	5mm shaft)/ set screw Gear, 14-T pinion (0.8 metric pitch, compatible with 32-pitch) (fits 5mm shaft)/ set screw Gear, 17-T pinion (0.8 metric pitch, compatible with 32-pitch) (fits 5mm shaft)/ set screw Gear, 18-T pinion (0.8 metric pitch, compatible with 32-pitch) (hardened steel) (fits 5mm shaft)/ set screw Gear, 20-T pinion (0.8 metric pitch, compatible with 32-pitch) (fits 5mm shaft)/ set screw Spur gear, steel, 50-tooth (0.8 metric pitch, compatible with 32-pitch) (for center differential) Spur gear, steel, 50-tooth (0.8 metric pitch, compatible with 32-pitch) (requires #6780 center differential) Screws, 3x8mm cap-head machine (hex drive) (6)/washers (6)/wrench Ball bearings (5x8x2.5mm) (2) Ball bearings, blue rubber sealed (5x8x2.5mm) (2) Drag link, machined 6061-T6 aluminum (blue-anodized)
2667 1664T 2656T 1664 2656 1765 2668 6863 6864 6862 6861 6857 6867 6868 6866 6866 6865	Rod ends, short (6)/ hollow balls (6) Shock caps, aluminum (Big Bore Shocks) (2) Shock shafts, hardened steel, titanium nitride coated (long) (2) Shock shafts, hardened steel, titanium nitride coated (xx-long) (2) Shock shafts, steel, chrome finish (long) (2) Shock shafts, steel, chrome finish (xx-long) (2) Silicone diaphragms (4) Spring retainers, upper & lower (2)/ spring pre-load spacers: 1mm (4)/ 1.5mm (2)/ 2mm (2)/ 4mm (2)/ 8mm (2) (Big Bore Shocks) Springs, front (progressive, +10% rate, pink) (2) Springs, front (progressive, -10% rate, pink) (2) Springs, front (progressive, -20% rate, orange) (2) Springs, front (white) (progressive rate) (2) Springs, rear (progressive, +10% rate, pink) (2) Springs, rear (progressive, +10% rate, pink) (2) Springs, rear (progressive, +10% rate, pink) (2) Springs, rear (progressive, -10% rate, pink) (2) Springs, rear (progressive, -20% rate, orange) (2)	5640 5643 5644 5646 6842X 3956X 1552 2728 5114	5mm shaft)/ set screw Gear, 14-T pinion (0.8 metric pitch, compatible with 32-pitch) (fits 5mm shaft)/ set screw Gear, 17-T pinion (0.8 metric pitch, compatible with 32-pitch) (fits 5mm shaft)/ set screw Gear, 18-T pinion (0.8 metric pitch, compatible with 32-pitch) (hardened steel) (fits 5mm shaft)/ set screw Gear, 20-T pinion (0.8 metric pitch, compatible with 32-pitch) (fits 5mm shaft)/ set screw Spur gear, steel, 50-tooth (0.8 metric pitch, compatible with 32-pitch) (for center differential) Spur gear, steel, 54-tooth (0.8 metric pitch, compatible with 32-pitch) (requires #6780 center differential) Screws, 3x8mm cap-head machine (hex drive) (6)/washers (6)/wrench Ball bearings (5x8x2.5mm) (2) Ball bearings, blue rubber sealed (5x8x2.5mm) (2)
2667 1664T 2656T 1664 2656 1765 2668 6863 6864 6862 6861 6857 6867 6868 6866	Rod ends, short (6)/ hollow balls (6) Shock caps, aluminum (Big Bore Shocks) (2) Shock shafts, hardened steel, titanium nitride coated (long) (2) Shock shafts, hardened steel, titanium nitride coated (xx-long) (2) Shock shafts, steel, chrome finish (long) (2) Shock shafts, steel, chrome finish (xx-long) (2) Silicone diaphragms (4) Spring retainers, upper & lower (2)/ spring pre-load spacers: 1mm (4)/ 1.5mm (2)/ 2mm (2)/ 4mm (2)/ 8mm (2) (Big Bore Shocks) Springs, front (progressive, +10% rate, pink) (2) Springs, front (progressive, +20% rate, blue) (2) Springs, front (progressive, -10% rate, green) (2) Springs, front (white) (progressive rate) (2) Springs, rear (progressive, +10% rate, blue) (2) Springs, rear (progressive, +20% rate, blue) (2) Springs, rear (progressive, +20% rate, blue) (2) Springs, rear (progressive, -20% rate, orange) (2) Springs, rear (white) (progressive rate) (2)	5640 5643 5644 5646 6842X 3956X 1552 2728 5114 6845A 6845G	Gear, 14-T pinion (0.8 metric pitch, compatible with 32-pitch) (fits 5mm shaft)/ set screw Gear, 17-T pinion (0.8 metric pitch, compatible with 32-pitch) (fits 5mm shaft)/ set screw Gear, 17-T pinion (0.8 metric pitch, compatible with 32-pitch) (fits 5mm shaft)/ set screw Gear, 18-T pinion (0.8 metric pitch, compatible with 32-pitch) (hardened steel) (fits 5mm shaft)/ set screw Gear, 20-T pinion (0.8 metric pitch, compatible with 32-pitch) (fits 5mm shaft)/ set screw Spur gear, steel, 50-tooth (0.8 metric pitch, compatible with 32-pitch) (for center differential) Spur gear, steel, 54-tooth (0.8 metric pitch, compatible with 32-pitch) (requires #6780 center differential) Signify Compatible Screws, 3x8mm cap-head machine (hex drive) (6)/washers (6)/wench Ball bearings (5x8x2.5mm) (2) Ball bearings, blue rubber sealed (5x8x2.5mm) (2) Drag link, machined 6061-T6 aluminum (blue-anodized) Drag link, machined 6061-T6 aluminum (green-anodized)
2667 1664T 2656T 1664 2656 1765 2668 6863 6864 6862 6861 6867 6868 6866 6865 6865 6858	Rod ends, short (6)/ hollow balls (6) Shock caps, aluminum (Big Bore Shocks) (2) Shock shafts, hardened steel, titanium nitride coated (long) (2) Shock shafts, hardened steel, titanium nitride coated (xx-long) (2) Shock shafts, steel, chrome finish (long) (2) Shock shafts, steel, chrome finish (xx-long) (2) Silicone diaphragms (4) Spring retainers, upper & lower (2)/ spring pre-load spacers: 1mm (4)/ 1.5mm (2)/ 2mm (2)/ 4mm (2)/ 8mm (2) (Big Bore Shocks) Springs, front (progressive, +10% rate, pink) (2) Springs, front (progressive, +20% rate, blue) (2) Springs, front (progressive, -20% rate, orange) (2) Springs, front (white) (progressive rate) (2) Springs, rear (progressive, +10% rate, pink) (2) Springs, rear (progressive, +20% rate, blue) (2) Springs, rear (progressive, -20% rate, orange) (2) Springs, rear (white) (progressive rate) (2)	5640 5643 5644 5646 6842X 3956X 1552 2728 5114 6845A 6845G 6845T 6845R 7438	5mm shaft)/ set screw Gear, 14-T pinion (0.8 metric pitch, compatible with 32-pitch) (fits 5mm shaft)/ set screw Gear, 17-T pinion (0.8 metric pitch, compatible with 32-pitch) (fits 5mm shaft)/ set screw Gear, 18-T pinion (0.8 metric pitch, compatible with 32-pitch) (hardened steel) (fits 5mm shaft)/ set screw Gear, 20-T pinion (0.8 metric pitch, compatible with 32-pitch) (fits 5mm shaft)/ set screw Spur gear, steel, 50-tooth (0.8 metric pitch, compatible with 32-pitch) (for center differential) Spur gear, steel, 54-tooth (0.8 metric pitch, compatible with 32-pitch) (requires #6780 center differential) Screws, 3x8mm cap-head machine (hex drive) (6)/washers (6)/wrench Ball bearings (5x8x2.5mm) (2) Ball bearings, blue rubber sealed (5x8x2.5mm) (2) Drag link, machined 6061-T6 aluminum (blue-anodized) Drag link, machined 6061-T6 aluminum (orange-anodized) Drag link, machined 6061-T6 aluminum (red-anodized) Linkage, steering
2667 1664T 2656T 1664 2656 1765 2668 6863 6864 6862 6861 6857 6867 6868 6866 6866 6865	Rod ends, short (6)/ hollow balls (6) Shock caps, aluminum (Big Bore Shocks) (2) Shock shafts, hardened steel, titanium nitride coated (long) (2) Shock shafts, hardened steel, titanium nitride coated (xx-long) (2) Shock shafts, steel, chrome finish (long) (2) Shock shafts, steel, chrome finish (xx-long) (2) Silicone diaphragms (4) Spring retainers, upper & lower (2)/ spring pre-load spacers: 1mm (4)/ 1.5mm (2)/ 2mm (2)/ 4mm (2)/ 8mm (2) (Big Bore Shocks) Springs, front (progressive, +10% rate, pink) (2) Springs, front (progressive, +20% rate, blue) (2) Springs, front (progressive, -10% rate, green) (2) Springs, front (white) (progressive rate) (2) Springs, rear (progressive, +10% rate, blue) (2) Springs, rear (progressive, +20% rate, blue) (2) Springs, rear (progressive, +20% rate, blue) (2) Springs, rear (progressive, -20% rate, orange) (2) Springs, rear (white) (progressive rate) (2)	5640 5643 5644 5646 6842X 3956X 1552 2728 5114 6845A 6845G 6845T 6845R 7438 2742X	Somm shaft)/ set screw Gear, 14-T pinion (0.8 metric pitch, compatible with 32-pitch) (fits 5mm shaft)/ set screw Gear, 17-T pinion (0.8 metric pitch, compatible with 32-pitch) (fits 5mm shaft)/ set screw Gear, 18-T pinion (0.8 metric pitch, compatible with 32-pitch) (hardened steel) (fits 5mm shaft)/ set screw Gear, 20-T pinion (0.8 metric pitch, compatible with 32-pitch) (fits 5mm shaft)/ set screw Spur gear, steel, 50-tooth (0.8 metric pitch, compatible with 32-pitch) (for center differential) Spur gear, steel, 54-tooth (0.8 metric pitch, compatible with 32-pitch) (requires #6780 center differential) Screws, 3x8mm cap-head machine (hex drive) (6)/washers (6)/wrench Ball bearings (5x8x2.5mm) (2) Ball bearings, blue rubber sealed (5x8x2.5mm) (2) Drag link, machined 6061-T6 aluminum (blue-anodized) Drag link, machined 6061-T6 aluminum (green-anodized) Drag link, machined 6061-T6 aluminum (green-anodized) Drag link, machined 6061-T6 aluminum (red-anodized) Linkage, steering Rod ends, short (6)/ hollow balls (6)
2667 1664T 2656T 1664 2656 1765 2668 6863 6864 6862 6861 6857 6867 6868 6866 6865 6858	Rod ends, short (6)/ hollow balls (6) Shock caps, aluminum (Big Bore Shocks) (2) Shock shafts, hardened steel, titanium nitride coated (long) (2) Shock shafts, hardened steel, titanium nitride coated (xx-long) (2) Shock shafts, steel, chrome finish (long) (2) Shock shafts, steel, chrome finish (xx-long) (2) Silicone diaphragms (4) Spring retainers, upper & lower (2)/ spring pre-load spacers: 1mm (4)/ 1.5mm (2)/ 2mm (2)/ 4mm (2)/ 8mm (2) (Big Bore Shocks) Springs, front (progressive, +10% rate, pink) (2) Springs, front (progressive, -10% rate, green) (2) Springs, front (progressive, -20% rate, orange) (2) Springs, front (white) (progressive rate) (2) Springs, rear (progressive, +10% rate, pink) (2) Springs, rear (progressive, -10% rate, pink) (2) Springs, rear (progressive, -10% rate, pink) (2) Springs, rear (progressive, -10% rate, pink) (2) Springs, rear (progressive, -20% rate, orange) (2) Springs, rear (progressive, -20% rate, orange) (2) Springs, rear (white) (progressive rate) (2) Springs, rear (white) (progressive rate) (2) Slight Sligh	5640 5643 5644 5646 6842X 3956X 1552 2728 5114 6845A 6845G 6845T 6845R 7438	5mm shaft)/ set screw Gear, 14-T pinion (0.8 metric pitch, compatible with 32-pitch) (fits 5mm shaft)/ set screw Gear, 17-T pinion (0.8 metric pitch, compatible with 32-pitch) (fits 5mm shaft)/ set screw Gear, 18-T pinion (0.8 metric pitch, compatible with 32-pitch) (hardened steel) (fits 5mm shaft)/ set screw Gear, 20-T pinion (0.8 metric pitch, compatible with 32-pitch) (fits 5mm shaft)/ set screw Spur gear, steel, 50-tooth (0.8 metric pitch, compatible with 32-pitch) (for center differential) Spur gear, steel, 54-tooth (0.8 metric pitch, compatible with 32-pitch) (requires #6780 center differential) Screws, 3x8mm cap-head machine (hex drive) (6)/washers (6)/wrench Ball bearings (5x8x2.5mm) (2) Ball bearings, blue rubber sealed (5x8x2.5mm) (2) Drag link, machined 6061-T6 aluminum (blue-anodized) Drag link, machined 6061-T6 aluminum (orange-anodized) Drag link, machined 6061-T6 aluminum (red-anodized) Linkage, steering
2667 1664T 2656T 1664 2656 1765 2668 6863 6864 6862 6861 6857 6867 6868 6866 6865 6858 3642 3765A 3766A 5475	Rod ends, short (6)/ hollow balls (6) Shock caps, aluminum (Big Bore Shocks) (2) Shock shafts, hardened steel, titanium nitride coated (long) (2) Shock shafts, hardened steel, titanium nitride coated (xx-long) (2) Shock shafts, steel, chrome finish (long) (2) Shock shafts, steel, chrome finish (xx-long) (2) Shock shafts, steel, chrome finish (xx-long) (2) Silicone diaphragms (4) Spring retainers, upper & lower (2)/ spring pre-load spacers: Imm (4)/ 1.5mm (2)/ 2mm (2)/ 4mm (2)/ 8mm (2) (Big Bore Shocks) Springs, front (progressive, +10% rate, pink) (2) Springs, front (progressive, +20% rate, blue) (2) Springs, front (progressive, -20% rate, orange) (2) Springs, front (white) (progressive rate) (2) Springs, rear (progressive, +10% rate, pink) (2) Springs, rear (progressive, +10% rate, pink) (2) Springs, rear (progressive, -10% rate, pink) (2) Springs, rear (progressive, -20% rate, orange) (2) Springs, rear (progressive, -20% rate, orange) (2) Springs, rear (white) (progressive rate) (2) Springs, rear (white) (progressive rate) (2) Attachment screws, shock (3x12mm shoulder screws) (6) Body, Ultra Shock(s) (long) (gray) (2) Body, Ultra Shock(s) (XXL) (gray) (2) Multi-tool (plastic)	5640 5643 5644 5646 6842X 3956X 1552 2728 5114 6845A 6845G 6845T 6845R 7438 2742X	Gear, 14-T pinion (0.8 metric pitch, compatible with 32-pitch) (fits 5mm shaft)/ set screw Gear, 17-T pinion (0.8 metric pitch, compatible with 32-pitch) (fits 5mm shaft)/ set screw Gear, 17-T pinion (0.8 metric pitch, compatible with 32-pitch) (fits 5mm shaft)/ set screw Gear, 18-T pinion (0.8 metric pitch, compatible with 32-pitch) (hardened steel) (fits 5mm shaft)/ set screw Gear, 20-T pinion (0.8 metric pitch, compatible with 32-pitch) (fits 5mm shaft)/ set screw Spur gear, steel, 50-tooth (0.8 metric pitch, compatible with 32-pitch) (for center differential) Spur gear, steel, 54-tooth (0.8 metric pitch, compatible with 32-pitch) (requires #6780 center differential) Screws, 3x8mm cap-head machine (hex drive) (6)/washers (6)/wrench Ball bearings (5x8x2.5mm) (2) Ball bearings, blue rubber sealed (5x8x2.5mm) (2) Drag link, machined 6061-T6 aluminum (blue-anodized) Drag link, machined 6061-T6 aluminum (orange-anodized) Drag link, machined 6061-T6 aluminum (red-anodized) Linkage, steering Rod ends, short (6)/ hollow balls (6) Steering bellcranks/ servo saver/ servo saver spring/ servo spring retainer/servo horn, steering Toe link, front & rear (molded composite) (2)/ hollow balls (4)
2667 1664T 2656T 1664 2656 1765 2668 6863 6864 6862 6861 6857 6867 6868 6866 6865 6858 3642 3765A 3766A 5475 2362	Rod ends, short (6)/ hollow balls (6) Shock caps, aluminum (Big Bore Shocks) (2) Shock shafts, hardened steel, titanium nitride coated (long) (2) Shock shafts, hardened steel, titanium nitride coated (xx-long) (2) Shock shafts, steel, chrome finish (long) (2) Shock shafts, steel, chrome finish (xx-long) (2) Slilicone diaphragms (4) Spring retainers, upper & lower (2)/ spring pre-load spacers: 1mm (4)/ 1.5mm (2)/ 2mm (2)/ 4mm (2)/ 8mm (2) (Big Bore Shocks) Springs, front (progressive, +10% rate, pink) (2) Springs, front (progressive, +20% rate, blue) (2) Springs, front (progressive, -10% rate, green) (2) Springs, front (white) (progressive rate) (2) Springs, rear (progressive, +10% rate, pink) (2) Springs, rear (progressive, +10% rate, pink) (2) Springs, rear (progressive, -20% rate, blue) (2) Springs, rear (progressive, -20% rate, orange) (2) Springs, rear (bit (progressive rate) (2) Springs, rear (progressive, -20% rate, orange) (2) Springs, rear (bit (progressive rate) (2) Springs, rear (bit (bit (progressive rate) (2) Springs, rear (bit (bit (bit (bit (bit (bit (bit (bit	5640 5643 5644 5646 6842X 3956X 1552 2728 5114 6845A 6845G 6845T 6845R 7438 2742X 6845X 6742	Smm shaft)/ set screw Gear, 14-T pinion (0.8 metric pitch, compatible with 32-pitch) (fits 5mm shaft)/ set screw Gear, 17-T pinion (0.8 metric pitch, compatible with 32-pitch) (fits 5mm shaft)/ set screw Gear, 18-T pinion (0.8 metric pitch, compatible with 32-pitch) (hardened steel) (fits 5mm shaft)/ set screw Gear, 20-T pinion (0.8 metric pitch, compatible with 32-pitch) (hardened steel) (fits 5mm shaft)/ set screw Gear, 20-T pinion (0.8 metric pitch, compatible with 32-pitch) (for center differential) Spur gear, steel, 50-tooth (0.8 metric pitch, compatible with 32-pitch) (for center differential) Spur gear, steel, 54-tooth (0.8 metric pitch, compatible with 32-pitch) (requires #6780 center differential) Screws, 3x8mm cap-head machine (hex drive) (6)/washers (6)/wrench Ball bearings (5x8x2.5mm) (2) Ball bearings, blue rubber sealed (5x8x2.5mm) (2) Drag link, machined 6061-T6 aluminum (blue-anodized) Drag link, machined 6061-T6 aluminum (orange-anodized) Drag link, machined 6061-T6 aluminum (red-anodized) Linkage, steering Rod ends, short (6)/ hollow balls (6) Steering bellcranks/ servo saver/ servo saver spring/ servo spring retainer/servo horn, steering Toe link, front & rear (molded composite) (2)/ hollow balls (4) (87mm center to center)
2667 1664T 2656T 1664 2656 1765 2668 6863 6864 6862 6861 6857 6867 6868 6866 6865 6858 3642 3765A 3766A 5475	Rod ends, short (6)/ hollow balls (6) Shock caps, aluminum (Big Bore Shocks) (2) Shock shafts, hardened steel, titanium nitride coated (long) (2) Shock shafts, hardened steel, titanium nitride coated (xx-long) (2) Shock shafts, steel, chrome finish (long) (2) Shock shafts, steel, chrome finish (xx-long) (2) Shock shafts, steel, chrome finish (xx-long) (2) Silicone diaphragms (4) Spring retainers, upper & lower (2)/ spring pre-load spacers: Imm (4)/ 1.5mm (2)/ 2mm (2)/ 4mm (2)/ 8mm (2) (Big Bore Shocks) Springs, front (progressive, +10% rate, pink) (2) Springs, front (progressive, +20% rate, blue) (2) Springs, front (progressive, -20% rate, orange) (2) Springs, front (white) (progressive rate) (2) Springs, rear (progressive, +10% rate, pink) (2) Springs, rear (progressive, +10% rate, pink) (2) Springs, rear (progressive, -10% rate, pink) (2) Springs, rear (progressive, -20% rate, orange) (2) Springs, rear (progressive, -20% rate, orange) (2) Springs, rear (white) (progressive rate) (2) Springs, rear (white) (progressive rate) (2) Attachment screws, shock (3x12mm shoulder screws) (6) Body, Ultra Shock(s) (long) (gray) (2) Body, Ultra Shock(s) (XXL) (gray) (2) Multi-tool (plastic)	5640 5643 5644 5646 6842X 3956X 1552 2728 5114 6845A 6845G 6845T 6845R 7438 2742X 6845X	Smm shaft)/ set screw Gear, 14-T pinion (0.8 metric pitch, compatible with 32-pitch) (fits 5mm shaft)/ set screw Gear, 17-T pinion (0.8 metric pitch, compatible with 32-pitch) (fits 5mm shaft)/ set screw Gear, 18-T pinion (0.8 metric pitch, compatible with 32-pitch) (hardened steel) (fits 5mm shaft)/ set screw Gear, 20-T pinion (0.8 metric pitch, compatible with 32-pitch) (hardened steel) (fits 5mm shaft)/ set screw Spur gear, steel, 50-tooth (0.8 metric pitch, compatible with 32-pitch) (for center differential) Spur gear, steel, 54-tooth (0.8 metric pitch, compatible with 32-pitch) (requires #6780 center differential) Screws, 3x8mm cap-head machine (hex drive) (6)/washers (6)/wrench Ball bearings (5x8x2.5mm) (2) Ball bearings, blue rubber sealed (5x8x2.5mm) (2) Drag link, machined 6061-T6 aluminum (blue-anodized) Drag link, machined 6061-T6 aluminum (green-anodized) Drag link, machined 6061-T6 aluminum (orange-anodized) Drag link, machined 6061-T6 aluminum (red-anodized) Linkage, steering Rod ends, short (6)/ hollow balls (6) Steering bellcranks/ servo saver/ servo saver spring/ servo spring retainer/servo horn, steering Toe link, front & rear (molded composite) (2)/ hollow balls (4) (87mm center to center) Toe links (TUBES blue-anodized, 7075-T6 aluminum, stronger
2667 1664T 2656T 1664 2656 1765 2668 6863 6864 6862 6861 6857 6867 6868 6866 6865 6858 3642 3765A 3766A 5475 2362 1942	Rod ends, short (6)/ hollow balls (6) Shock caps, aluminum (Big Bore Shocks) (2) Shock shafts, hardened steel, titanium nitride coated (long) (2) Shock shafts, hardened steel, titanium nitride coated (xx-long) (2) Shock shafts, steel, chrome finish (long) (2) Shock shafts, steel, chrome finish (xx-long) (2) Shock shafts, steel, chrome finish (xx-long) (2) Silicone diaphragms (4) Spring retainers, upper & lower (2)/ spring pre-load spacers: 1mm (4)/ 1.5mm (2)/ 2mm (2)/ 4mm (2)/ 8mm (2) (Big Bore Shocks) Springs, front (progressive, +10% rate, pink) (2) Springs, front (progressive, +20% rate, blue) (2) Springs, front (progressive, -10% rate, green) (2) Springs, front (white) (progressive rate) (2) Springs, rear (progressive, +10% rate, pink) (2) Springs, rear (progressive, +10% rate, pink) (2) Springs, rear (progressive, -10% rate, orange) (2) Springs, rear (progressive, -20% rate, orange) (2) Springs, rear (white) (progressive rate) (2) Springs, rear (white) (progressive rate) (2) Slock Sillica Slock (3x12mm shoulder screws) (6) Body, Ultra Shock(s) (long) (gray) (2) Multi-tool (plastic) Rebuild kit, Ultra shocks (for 2 shocks) Rod ends (16 long & 4 short)/ hollow ball connectors (18)/ ball screws (2) Rod ends, short (6)/ hollow balls (6)	5640 5643 5644 5646 6842X 3956X 1552 2728 5114 6845A 6845G 6845T 6845R 7438 2742X 6845X 6742	Gear, 14-T pinion (0.8 metric pitch, compatible with 32-pitch) (fits 5mm shaft)/ set screw Gear, 17-T pinion (0.8 metric pitch, compatible with 32-pitch) (fits 5mm shaft)/ set screw Gear, 17-T pinion (0.8 metric pitch, compatible with 32-pitch) (hardened steel) (fits 5mm shaft)/ set screw Gear, 20-T pinion (0.8 metric pitch, compatible with 32-pitch) (hardened steel) (fits 5mm shaft)/ set screw Gear, 20-T pinion (0.8 metric pitch, compatible with 32-pitch) (for center differential) Spur gear, steel, 50-tooth (0.8 metric pitch, compatible with 32-pitch) (for center differential) Spur gear, steel, 54-tooth (0.8 metric pitch, compatible with 32-pitch) (requires #6780 center differential) Signify Compatible Screws, 3x8mm cap-head machine (hex drive) (6)/washers (6)/wench Ball bearings (5x8x2.5mm) (2) Ball bearings, blue rubber sealed (5x8x2.5mm) (2) Drag link, machined 6061-T6 aluminum (blue-anodized) Drag link, machined 6061-T6 aluminum (green-anodized) Drag link, machined 6061-T6 aluminum (red-anodized) Linkage, steering Rod ends, short (6)/ hollow balls (6) Steering bellcranks/ servo saver/ servo saver spring/ servo spring retainer/servo horn, steering Toe link, front & rear (molded composite) (2)/ hollow balls (4) (87mm center to center) Toe links (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (87mm) (2)/ rod ends (4)/ aluminum wrench (1) Toe links (TUBES green-anodized, 7075-T6 aluminum, stronger
2667 1664T 2656T 1664 2656 1765 2668 6863 6864 6862 6861 6867 6867 6868 6866 6865 6858 3642 3765A 3766A 5475 2362 1942 2742X 3767	Rod ends, short (6)/ hollow balls (6) Shock caps, aluminum (Big Bore Shocks) (2) Shock shafts, hardened steel, titanium nitride coated (long) (2) Shock shafts, hardened steel, titanium nitride coated (xx-long) (2) Shock shafts, steel, chrome finish (long) (2) Shock shafts, steel, chrome finish (xx-long) (2) Shock shafts, steel, chrome finish (xx-long) (2) Silicone diaphragms (4) Spring retainers, upper & lower (2)/ spring pre-load spacers: 1mm (4)/ 1.5mm (2)/ 2mm (2)/ 4mm (2)/ 8mm (2) (Big Bore Shocks) Springs, front (progressive, +10% rate, pink) (2) Springs, front (progressive, +20% rate, blue) (2) Springs, front (progressive, -10% rate, green) (2) Springs, front (progressive, -20% rate, orange) (2) Springs, rear (progressive, +10% rate, pink) (2) Springs, rear (progressive, +20% rate, blue) (2) Springs, rear (progressive, -10% rate, green) (2) Springs, rear (progressive, -20% rate, orange) (2) Springs, rear (progressive, -20% rate, orange) (2) Springs, rear (progressive, -20% rate, orange) (2) Springs, rear (white) (progressive rate) (2) Shock (3x12mm shoulder screws) (6) Body, Ultra Shock(s) (long) (gray) (2) Body, Ultra Shock(s) (XXL) (gray) (2) Multi-tool (plastic) Rebuild kit, Ultra shocks (for 2 shocks) Rod ends (16 long & 4 short)/ hollow ball connectors (18)/ ball screws (2) Rod ends, short (6)/ hollow balls (6) Shock caps (2)/ shock bottoms (2)	5640 5643 5644 5646 6842X 3956X 1552 2728 5114 6845A 6845G 6845T 6845R 7438 2742X 6845X 6742 6742Z 6742G	Gear, 14-T pinion (0.8 metric pitch, compatible with 32-pitch) (fits 5mm shaft)/ set screw Gear, 17-T pinion (0.8 metric pitch, compatible with 32-pitch) (fits 5mm shaft)/ set screw Gear, 17-T pinion (0.8 metric pitch, compatible with 32-pitch) (hardened steel) (fits 5mm shaft)/ set screw Gear, 20-T pinion (0.8 metric pitch, compatible with 32-pitch) (hardened steel) (fits 5mm shaft)/ set screw Gear, 20-T pinion (0.8 metric pitch, compatible with 32-pitch) (fits 5mm shaft)/ set screw Spur gear, steel, 50-tooth (0.8 metric pitch, compatible with 32-pitch) (for center differential) Spur gear, steel, 54-tooth (0.8 metric pitch, compatible with 32-pitch) (requires #6780 center differential) Screws, 3x8mm cap-head machine (hex drive) (6)/washers (6)/wrench Ball bearings (5x8x2.5mm) (2) Ball bearings, blue rubber sealed (5x8x2.5mm) (2) Drag link, machined 6061-T6 aluminum (blue-anodized) Drag link, machined 6061-T6 aluminum (orange-anodized) Drag link, machined 6061-T6 aluminum (red-anodized) Linkage, steering Rod ends, short (6)/ hollow balls (6) Steering bellcranks/ servo saver/ servo saver spring/ servo spring retainer/servo horn, steering Toe link, front & rear (molded composite) (2)/ hollow balls (4) (87mm center to center) Toe links (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (87mm) (2)/ rod ends (4)/ aluminum wrench (1)
2667 1664T 2656T 1664 2656 1765 2668 6863 6864 6862 6861 6857 6867 6868 6866 6865 6858 3642 3765A 3766A 5475 2362 1942	Rod ends, short (6)/ hollow balls (6) Shock caps, aluminum (Big Bore Shocks) (2) Shock shafts, hardened steel, titanium nitride coated (long) (2) Shock shafts, hardened steel, titanium nitride coated (xx-long) (2) Shock shafts, steel, chrome finish (long) (2) Shock shafts, steel, chrome finish (xx-long) (2) Shock shafts, steel, chrome finish (xx-long) (2) Silicone diaphragms (4) Spring retainers, upper & lower (2)/ spring pre-load spacers: 1mm (4)/ 1.5mm (2)/ 2mm (2)/ 4mm (2)/ 8mm (2) (Big Bore Shocks) Springs, front (progressive, +10% rate, pink) (2) Springs, front (progressive, +20% rate, blue) (2) Springs, front (progressive, -10% rate, green) (2) Springs, front (white) (progressive rate) (2) Springs, rear (progressive, +10% rate, pink) (2) Springs, rear (progressive, +10% rate, pink) (2) Springs, rear (progressive, -10% rate, orange) (2) Springs, rear (progressive, -20% rate, orange) (2) Springs, rear (white) (progressive rate) (2) Springs, rear (white) (progressive rate) (2) Slock Sillica Slock (3x12mm shoulder screws) (6) Body, Ultra Shock(s) (long) (gray) (2) Multi-tool (plastic) Rebuild kit, Ultra shocks (for 2 shocks) Rod ends (16 long & 4 short)/ hollow ball connectors (18)/ ball screws (2) Rod ends, short (6)/ hollow balls (6)	5640 5643 5644 5646 6842X 3956X 1552 2728 5114 6845A 6845G 6845T 6845R 7438 2742X 6845X 6742 6742X	Gear, 14-T pinion (0.8 metric pitch, compatible with 32-pitch) (fits 5mm shaft)/ set screw Gear, 17-T pinion (0.8 metric pitch, compatible with 32-pitch) (fits 5mm shaft)/ set screw Gear, 17-T pinion (0.8 metric pitch, compatible with 32-pitch) (hardened steel) (fits 5mm shaft)/ set screw Gear, 20-T pinion (0.8 metric pitch, compatible with 32-pitch) (hardened steel) (fits 5mm shaft)/ set screw Gear, 20-T pinion (0.8 metric pitch, compatible with 32-pitch) (for center differential) Spur gear, steel, 50-tooth (0.8 metric pitch, compatible with 32-pitch) (for center differential) Spur gear, steel, 54-tooth (0.8 metric pitch, compatible with 32-pitch) (requires #6780 center differential) Signify Compatible Screws, 3x8mm cap-head machine (hex drive) (6)/washers (6)/wench Ball bearings (5x8x2.5mm) (2) Ball bearings, blue rubber sealed (5x8x2.5mm) (2) Drag link, machined 6061-T6 aluminum (blue-anodized) Drag link, machined 6061-T6 aluminum (green-anodized) Drag link, machined 6061-T6 aluminum (red-anodized) Linkage, steering Rod ends, short (6)/ hollow balls (6) Steering bellcranks/ servo saver/ servo saver spring/ servo spring retainer/servo horn, steering Toe link, front & rear (molded composite) (2)/ hollow balls (4) (87mm center to center) Toe links (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (87mm) (2)/ rod ends (4)/ aluminum wrench (1) Toe links (TUBES green-anodized, 7075-T6 aluminum, stronger

Page 5 Hoss™ 4X4 VXL: TQi Traxxas Link Enabled 2.4GHz Radio & TSM (Model 90076-4) Parts List

	Cuspension Linkons	8712	Speed Bit Essentials Set, hex and nut driver, 7-piece, includes
	Suspension Linkage	0712	premium handle (medium), travel pouch, hex drivers (straight:
3643X	Camber links, front (TUBES blue-anodized, 7075-T6 aluminum,		1.5mm, 2.0mm, 2.5mm) and nut drivers (5.0mm, 5.5mm, 7.0mm,
	stronger than titanium) (83mm) (2)/ rod ends (4)/ aluminum wrench (1) (#2579 3x15 BCS (4) required for installation)		and 8.0mm), 1/4" drive
3643G	Camber links, front (TUBES green-anodized, 7075-T6 aluminum,	8721	Speed bit handle, medium (one piece)
00-100	stronger than titanium) (83mm) (2)/ rod ends (4)/ aluminum	8720 8722	Speed bit handle, premium, large (rubber overmold) Speed bit handle, premium, medium (rubber overmold)
	wrench (1) (#2579 3x15 BCS (4) required for installation)	8710	Speed bit Master Set, hex and nut driver, 13-piece, includes
3643R	Camber links, front (TUBES red-anodized, 7075-T6 aluminum,	07.10	premium handle (medium), travel pouch, hex drivers (straight:
	stronger than titanium) (83mm) (2)/ rod ends (4)/ aluminum		1.5mm, 2.0mm, 2.5mm, 3.0mm), (ball-end: 2.0mm, 2.5mm,
3644X	wrench (1) (#2579 3x15 BCS (4) required for installation) Camber links, rear (TUBES blue-anodized, 7075-T6 aluminum,		3.0mm), and nut drivers (4.00mm, 4.50mm, 5.00mm, 5.50mm,
JU44X	stronger than titanium) (73mm) (2)/ rod ends (4)/ aluminum	0744	7.00mm, 8.00mm),
	wrench (1) (#2579 3x15 BCS (4) required for installation)	8711	Speed Bit Master Set, hex driver, 7-piece straight and ball end, includes premium handle (medium), travel pouch, hex drivers
3644G	Camber links, rear (TUBES green-anodized 7075-T6 aluminum,		(straight: 1.5mm, 2.0mm, 2.5mm, 3.0mm) (ball end: 2.0mm,
	stronger than titanium) (73mm) (2)/ rod ends (4)/ aluminum		2.5mm, 3.0mm), 1/4" drive
3644R	wrench (1) (#2579 3x15 BCS (4) required for installation)	8719	Speed Bit Master Set, nut driver, 6-piece, includes premium
3044K	Camber links, rear (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (73mm) (2)/ rod ends (4)/ aluminum		handle (medium), travel pouch, and nut drivers (4.0mm, 4.5mm,
	wrench (1) (#2579 3x15 BCS (4) required for installation)	8716	5.0mm, 5.5mm, 7.0mm, 8.0mm), 1/4" drive
5525	Rod ends (12)/ hollow balls (12)	0/10	Speed Bit Set, hex driver, 2-piece ball-end (2.0mm, 2.5mm), 1/4" drive
3739	Screw pin set (Rustler®/ Bandit/ Stampede®)	8716X	Speed Bit Set, hex driver, 3-piece ball-end (2.0mm, 2.5mm,
6834	Suspension pin set, complete (front and rear)		3.0mm), 1/4" drive
2537	Threaded rods (20/25/44mm 1 ea.)/ (1) 12mm set screw	8715	Speed Bit Set, hex driver, 3-piece straight (1.5mm, 2.0mm,
6742X	Toe links (TUBES blue-anodized, 7075-T6 aluminum, stronger		2.5mm), 1/4" drive
6742G	than titanium) (87mm) (2)/ rod ends (4)/ aluminum wrench (1) Toe links (TUBES green-anodized, 7075-T6 aluminum, stronger	8715X	Speed Bit Set, hex driver, 4-piece straight (1.5mm, 2.0mm,
07420	than titanium) (87mm) (2)/ rod ends (4)/ aluminum wrench (1)	3415	2.5mm, 3.0mm), 1/4" drive Tool set with pouch (includes 1.5mm, 2.0mm, 2.5mm, 3.0mm,
6742R	Toe links (TUBES red-anodized, 7075-T6 aluminum, stronger	3415	3.5mm, 4mm drivers/ 4mm, 5mm, 5.5mm, 7mm and 8mm nut
	than titanium) (87mm) (2)/ rod ends (4)/ aluminum wrench (1)		drivers/ 2mm, 4mm, and 5mm slotted screwdrivers/ #00 Phillips,
3644	Turnbuckles, camber link, 39mm (69mm center to center) (assembled		#0 Phillips, and #1 Phillips screwdrivers/ 4mm and 8mm wrench/
	with rod ends and hollow balls) (1 left, 1 right) (fits front & rear on		driver handle
3643	Slash) Turnbuckles, camber link, 49mm (82mm center to center) (assembled		Turnbuckles & Threaded Rods
3043	with rod ends and hollow balls) (1 left, 1 right)	3643X	Camber links, front (TUBES blue-anodized, 7075-T6 aluminum,
5539	Turnbuckles, camber links, 58mm (assembled with rod ends and		stronger than titanium) (83mm) (2)/ rod ends (4)/ aluminum
	hollow balls) (2)		wrench (1) (#2579 3x15 BCS (4) required for installation)
	Team Traxxas Items	3643G	Camber links, front (TUBES green-anodized, 7075-T6 aluminum,
2514	Decal sheet, racing sponsors		stronger than titanium) (83mm) (2)/ rod ends (4)/ aluminum wrench (1) (#2579 3x15 BCS (4) required for installation)
6160X	DVD, Maxx® Power! Full Throttle Action (sleeve)	3643R	Camber links, front (TUBES red-anodized, 7075-T6 aluminum,
9950	Official Team Traxxas® racing decal set (flag logo/ 6-color)		stronger than titanium) (83mm) (2)/ rod ends (4)/ aluminum
9909	Traxxas® racing banner, red & black (3x7 feet)		wrench (1) (#2579 3x15 BCS (4) required for installation)
	Tires & Wheels	3644X	Camber links, rear (TUBES blue-anodized, 7075-T6 aluminum,
5116	Ball bearings, blue rubber sealed (5x11x4mm) (2)		stronger than titanium) (73mm) (2)/ rod ends (4)/ aluminum wrench (1) (#2579 3x15 BCS (4) required for installation)
3647	Nuts, 4mm flanged nylon locking (steel, serrated) (8)	3644G	Camber links, rear (TUBES green-anodized 7075-T6 aluminum,
1747R	Nuts, aluminum, flanged, serrated (4mm) (blue-anodized) (4)	00110	stronger than titanium) (73mm) (2)/ rod ends (4)/ aluminum
1985	PTFE-coated washers, 5x8x0.5mm (20) (use with ball bearings)		wrench (1) (#2579 3x15 BCS (4) required for installation)
1647	Silicone grease	3644R	Camber links, rear (TUBES red-anodized, 7075-T6 aluminum,
2754	Stub axle pins (4)		stronger than titanium) (73mm) (2)/ rod ends (4)/ aluminum
4175	Tires & wheels, assembled, glued (2.8") (All-Star black chrome	EEDE	wrench (1) (#2579 3x15 BCS (4) required for installation)
	wheels, paddle tires, foam inserts) (nitro rear/ 4WD electric	5525 6742	Rod ends (12)/ hollow balls (12) Toe link, front & rear (molded composite) (2)/ hollow balls (4)
3669A	front/rear) (2) (TSM rated) Tires & wheels, assembled, glued (2.8") (All-Star black chrome	0742	(87mm center to center)
3000A	wheels, Talon tires, foam inserts) (nitro rear/ electric front) (2)	6742X	Toe links (TUBES blue-anodized, 7075-T6 aluminum, stronger
	(TSM rated)		than titanium) (87mm) (2)/ rod ends (4)/ aluminum wrench (1)
3669	Tires & wheels, assembled, glued (2.8") (All-Star chrome wheels,	6742G	Toe links (TUBES green-anodized, 7075-T6 aluminum, stronger
	Talon tires, foam inserts) (nitro rear/ electric front) (2)	07.455	than titanium) (87mm) (2)/ rod ends (4)/ aluminum wrench (1)
6792	Tires & wheels, assembled, glued (black 2.8" wheels,	6742R	Toe links (TUBES red-anodized, 7075-T6 aluminum, stronger
0070	Sledgehammer™ tires, foam inserts) (2) (TSM® rated)	3644	than titanium) (87mm) (2)/ rod ends (4)/ aluminum wrench (1) Turnbuckles, camber link, 39mm (69mm center to center) (assembled
9072	Tires & wheels, assembled, glued (black chrome 2.8" wheels, Sledgehammer™ tires, foam inserts) (2) (TSM® rated)	3644	with rod ends and hollow balls) (1 left, 1 right) (fits front & rear on
3665X	Tires & wheels, assembled, glued (chrome wheels, Terra Groove		Slash)
JUJUA	dual profile tires, foam inserts) (nitro rear/ electric front) (2)	3643	Turnbuckles, camber link, 49mm (82mm center to center) (assembled
3665	Tires & wheels, assembled, glued (satin chrome wheels, Terra		with rod ends and hollow balls) (1 left, 1 right)
	Groove dual profile tires, foam inserts) (nitro rear/ electric front)	5539	Turnbuckles, camber links, 58mm (assembled with rod ends and
	(2)		hollow balls) (2)
6771	Tires and wheels, assembled, glued 2.8" (All-Star chrome		
6760	wheels, Maxx® tires, foam inserts) (2)		
6769 1654	Tires, Talon EXT 2.8" (2)/ foam inserts (2)		
1654X	Wheel hubs, hex (rear) (2)/ stub axle pins (2) Wheel hubs, hex (blue-anodized, lightweight aluminum) (2)/ axle		If you have questions or need technical assistance, call Traxxas at:
.007/	pins(4)		
6856X	Wheel hubs, splined, 17mm, short (4)/ wheel nuts, splined, 17mm		1 <i>-888-TRAXXAS</i>
	(4) (blue-anodized)/ hub retainer M4 X 0.7 (4)/ axle pin (4)/		(1-888-872-9927) (U.S. residents only)
0770	wrench, 5mm		For orders, calls outside the U.S., and other information, call 972-549-3000,
6772	Wheels, RXT 2.8" (black) (2)		or fax to 972-549-3011 e-mail Traxxas at support@Traxxas.com

Traxxas Tools

Body reamer (aluminum handle) Body reamer (plastic handle) Cap, body reamer

Scissors, curved tip

Scissors, straight tip

3433X

3433 3436 3432

3431

TRAXXAS.COM